

REIGN ADVANCED E+ 2

GIANT



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
STEUEREINHEIT	Giant RideControl Ergo 4
DISPLAY	Giant RideControl GO Lux
AKKU	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Moon Dust
RAHMEN	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
GABEL	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
DÄMPFER	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMPONENTEN	
LENKER	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
GRIFFE	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170,L/XL: 170-200) MMX remote
SATTEL	Giant Romero, Neutral
ANTRIEB	
SCHALTHEBEL	Shimano Deore
SCHALTWERK	Shimano Deore, 12-speed shadow+
BREMSSEN	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
BREMSHEBEL	Shimano SLX
KASSETTE	Shimano Deore, 10-51T, 12-speed
KETTE	Shimano Deore 12-speed
KURBEL	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

LAUFRÄDER	
FELGEN	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
NABE	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
SPEICHEN	Sapim Race [F] E-Lite [R], e-bike optimized
REIFEN	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Aegis Tire Checker
ACCESSORIES	
BELEUCHTUNG	Optional: - Giant Recon series e-bike lights available and direct connectable

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	235			260			285			310		
Sitzrohrwinkel	77.1°	77.5°	77.9°	77.1°	77.5°	77.9°	77.1°	77.5°	77.9°	77.1°	77.5°	
Oberrohrlänge (mm)	570	569	568	602	601	600	625	624	623	657	656	655
Steuerrohr-Länge (mm)	95			105			120			135		
Steuerrohr-Winkel	63.1°	63.5°	63.9°	63.1°	63.5°	63.9°	63.1°	63.5°	63.9°	63.1°	63.5°	
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	133.3	130.3	127.4	133.3	130.3	127.4	133.3	130.3	127.4	133.3	130.3	
Radstand (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323	1323	
Kettenstreben-Länge (mm)	450	450	450	450	450	450	450	450	450	450	450	450
Tretlager-Höhe (mm)	10	5		10	5		10	5		10	5	
Stack (mm)	647	645	642	656	654	651	669	667	665	683	680	678
Reach (mm)	426	430	435	456	460	465	476	480	485	505	510	515
Lenkerbreite (mm)	800			800			800			800		
Vorbaulänge (mm)	40			40			40			40		
Kurbellänge (mm)	160			160			160			160		
Radgrösse	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Spezifikations-, Preis- und Farbänderungen vorbehalten.