



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
CONTROLLER	Giant RideControl Ergo 4
DISPLAY	Giant RideControl GO Lux
BATTERY	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, L, XL
ΧΡΩΜΑΤΑ	Moon Dust
ΣΚΕΛΕΤΟΣ	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
ΠΙΠΟΥΝΙ	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
ΑΝΑΡΤΗΣΗ	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact SL 35
ΛΑΙΜΟΣ ΣΤΕΛΛΑΣ	Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote
ΣΤΕΛΛΑ	Giant Romero, Neutral
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano Deore
ΝΤΕΡΑΓΓΙΕΡ ΟΠΙΣΘΙΟ.	Shimano Deore, 12-speed shadow+
ΦΡΕΝΑ	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano SLX
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano Deore, 10-51T, 12-speed
ΑΛΥΣΙΔΑ	Shimano Deore 12-speed
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
ΚΕΝΤΡΑ	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
ΑΚΤΙΝΕΣ	Sapim Race [F] E-Lite [R], e-bike optimized
ΕΛΑΣΤΙΚΑ	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Aegis Tire Checker
ACCESSORIES	
LIGHTING	Optional: - Giant Recon series e-bike lights available and direct connectable

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	235			260			285			310		
Seat Tube Angle	77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°		
Top Tube Length (mm)	570 569 568			602 601 600			625 624 623			657 656 655		
Head Tube Length (mm)	95			105			120			135		
Head Tube Angle	63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	133,3 130,3 127,4			133,3 130,3 127,4			133,3 130,3 127,4			133,3 130,3 127,4		
Wheelbase (mm)	1226 1226 1227			1261 1261 1261			1287 1288 1288			1323 1323 1323		
Chain Stay Length (mm)	450 450 450			450 450 450			450 450 450			450 450 450		
Bottom Bracket Drop (mm)	10 5			10 5			10 5			10 5		
Stack (mm)	647 645 642			656 654 651			669 667 665			683 680 677		
Reach (mm)	426 430 435			456 460 465			476 480 485			505 510 515		
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	160			160			160			160		
Wheel Size	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση