

REIGN ADVANCED E+ 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
CONTROLLER	Giant RideControl Ergo 4
DISPLAY	Giant RideControl Go Lux
BATTERY	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
CHARGER	Giant EnergyPak 4A Charger, 48V
FRAME	
FRAME	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
FORK	RockShox Zeb select, 29", 180mm travel, Delta RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
SHOCK	RockShox SuperDeluxe Select, RT, 205x65mm, custom tuned, 30% sag recommended
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 35mm rize, Up: 5° Back: 9°, 35x800mm
GRIPS	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
STEM	Giant Contact SL 35, 40 mm
SEATPOST	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SADDLE	Giant Romero, neutral
DRIVETRAIN	
SHIFTERS	Shimano Deore, 12-speed
REAR DERAILLEUR	Shimano Deore, RD-7200,12-speed Shadow+
BRAKES	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F/R]
BRAKE LEVERS	TRP EVO Comp
CASSETTE	Shimano Deore, HyperGlide+, 12-speed, 11-51T
CHAIN	Shimano Deore, 12-speed
CRANKSET	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

WHEELS	
RIMS	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
HUBS	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
SPOKES	Sapim Race [F] E-Lite [R], e-bike optimized
TIRES	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
EXTRAS	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

Suggested Retail Price (CDN): \$8,699.00

FRAME GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Angle	77.1°	77.5°	77.9°	77.5°	77.9°	77.1°	77.5°	77.9°
Top Tube Length (mm)	570	569	568	601	600	625	624	623
Head Tube Length (mm)	95			105		120		135
Head Tube Angle	63.1°	63.5°	63.9°	63.5°	63.9°	63.1°	63.5°	63.9°
Wheelbase (mm)	1226	1226	1227	1261	1261	1287	1288	1288
Chain Stay Length (mm)	450	450	450	450	450	450	450	450
Stack (mm)	647	645	642	654	651	669	667	665
Reach (mm)	426	430	435	460	465	476	480	485
Crank Length (mm)	155			155		155		155

All prices and specifications are subject to change without notice.