

REIGN ADVANCED E+ 2

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Ergo 4
DISPLAY	Giant RideControl GO Lux
BATERÍA	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONECTIVIDAD	Aegis Tire Checker included in RideControl display
CUADRO	
TALLAS	S, M, L, XL
COLORES	Moon Dust
CUADRO	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
TIJERA	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
AMORTIGUADOR	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
COMPONENTES	
MANUBRIO	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCIA	Giant Contact SL 35
POSTE DE ASIENTO	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170,L/XL: 170-200) MMX remote
ASIENTO	Giant Romero, Neutral
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore
CAMBIO TRASERO	Shimano Deore, 12-speed shadow+
FRENOS	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
PALANCAS DE FRENOS	Shimano SLX
CASSETTE	Shimano Deore, 10-51T, 12-speed
CADENA	Shimano Deore 12-speed
MULTIPLICACIÓN	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

RUEDAS	
RUEDAS	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
MAZAS	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
RAYOS	Sapim Race [F] E-Lite [R], e-bike optimized
NEUMÁTICOS	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Aegis Tire Checker
ACCESORIOS	
LUCES	Optional: - Giant Recon series e-bike lights available and direct connectable

Precio: \$179,990.00

GEOMETRÍA

CUADRO	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longitud de la Base del Poste de Asiento (mm)	400			425			450		
Seat Post Insertion Depth (mm)	235			260			285		
Ángulo de la Base del Poste de Asiento	77.1°	77.5°	77.9°	77.1°	77.5°	77.9°	77.1°	77.5°	77.9°
Longitud del Tubo Superior (mm)	570	569	568	602	601	600	625	624	623
Longitud del Telescopio (mm)	95			105			120		
Ángulo del Telescopio	63.1°	63.5°	63.9°	63.1°	63.5°	63.9°	63.1°	63.5°	63.9°
Rake (mm)	44			44			44		
Trail (mm)	133.3	130.3	127.4	133.3	130.3	127.4	133.3	130.3	127.4
Distancia entre Ejes (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288
Longitud de Vaina Inferior (mm)	450	450	450	450	450	450	450	450	450
Caída del Eje de Centro (mm)	10	5		10	5		10	5	
Stack (mm)	647	645	642	656	654	651	669	667	665
Reach (mm)	426	430	435	456	460	465	476	480	485
Ancho del Manubrio (mm)	800			800			800		
Longitud de la Potencia (mm)	40			40			40		
Longitud de la Biela (mm)	160			160			160		
Tamaño de las Ruedas	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Todas las especificaciones están sujetas a cambios sin previo aviso.