

REIGN ADVANCED E+ 2



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
OHJAUSYKSIKKÖ	Giant RideControl Ergo 4
NÄYTTÖ	Giant RideControl GO Lux
AKKU	Giant EnergyPak Smart 560Wh, integrated, 48V
LATURI	Giant EnergyPak smart charger 4A, 48V
YHTEYDET MUIHIN LAITTEISIIN	Aegis Tire Checker included in RideControl display
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Moon Dust
RUNKO	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
HAARUKKA	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
ISKUNVAIMENNIN	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMONENTIT	
OHJAUSTANKO	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
GRIPIT	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
OHJAINKANNATIN	Giant Contact SL 35
SATULATOLPPA	Giant Contact Switch adjustable dropper, 30,9mm (S:110–140, M:140–170, L/XL: 170–200) MMX remote
SATULA	Giant Romero, Neutral
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore
TAKAVAIHTAJA	Shimano Deore, 12-speed shadow+
JARRUT	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
JARRUKAHVAT	Shimano SLX
RATASPAKKA	Shimano Deore, 10-51T, 12-speed
KETJUT	Shimano Deore 12-speed
KAMPISARJA	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

RENKAAT	
VANTEET	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
NAVAT	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
PINNAT	Sapim Race [F] E-Lite [R], e-bike optimized
RENKAAT	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
LISÄTIEDOT	Aegis Tire Checker
TARVIKKEET	
VALOT	Optional: - Giant Recon series e-bike lights available and direct connectable

Suositusinta: 7 099,00 €

GEOMETRIA

RUNKO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Satulaputken pituus (mm)	400			425			450			475
Satulatolpan asennussyvyys (mm)	235			260			285			310
Satulaputken kulma	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°
Vaakaputken pituus (mm)	570	569	568	602	601	600	625	624	623	657
Emäputken pituus (mm)	95			105			120			135
Emäputken kulma	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°
Haarukan offset (mm)	44			44			44			44
Trail-mitta (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3
Akseliväli (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323
Takahaarukan alaputken pituus (mm)	450	450	450	450	450	450	450	450	450	450
Keskiön pudotus (mm)	10	5		10	5		10	5		10
Stack-mitta (mm)	647	645	642	656	654	651	669	667	665	683
Reach-mitta (mm)	426	430	435	456	460	465	476	480	485	505
Ohjaustangon leveys (mm)	800			800			800			800
Ohjainkannattimen pituus (mm)	40			40			40			40
Kammen pituus (mm)	160			160			160			160
Rengaskoko	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.