REIGN ADVANCED E+ 2



TEKNISET TIEDOT

E+ SYSTEM	
MOOTTORI	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
OHJAUSYKSIKKÖ	Giant RideControl Ergo 4
NÄYTTÖ	Giant RideControl Go Lux
AKKU	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
LATURI	Giant EnergyPak 4A Charger, 48V
RUNKO	
RUNKO	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
HAARUKKA	RockShox Zeb select, 29", 180mm travel, Delta RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
ISKUNVAIMENNIN	RockShox SuperDeluxe Select, RT, 205x65mm, custom tuned, 30% sag recommended
KOMPONENTIT	
OHJAUSTANKO	Giant Contact TR35, 35mm rize, Up: 5º Back: 9º, 35x800mm
GRIPIT	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
OHJAINKANNATIN	Giant Contact SL 35, 40 mm
SATULATOLPPA	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SATULA	Giant Romero, neutral
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore, 12-speed
TAKAVAIHTAJA	Shimano Deore, RD-7200,12-speed Shadow+
JARRUT	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F/R]
JARRUKAHVAT	TRP EVO Comp
RATASPAKKA	Shimano Deore, HyperGlide+, 12-speed, 11-51T
KETJUT	Shimano Deore, 12-speed
KAMPISARJA	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

RENKAAT	
VANTEET	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
NAVAT	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
PINNAT	Sapim Race [F] E-Lite [R], e-bike optimized
RENKAAT	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
LISÄTIEDOT	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
TARVIKKEET	
VALOT	Optional: Giant Recon series e-bike lights available and direct-connect compatible
RAJOITTEET	
COMBINED MAXIMUM LOAD LIMIT	156kg

Suositushinta: 7 439,00 €

GEOMETRIA

RUNKO	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Satulaputken kulma	77,1° | 77,5° | 77,9°	77,5° | 77,9°	77,1° | 77,5° | 77,9°	77,1° | 77,5° | 77,
Vaakaputken pituus (mm)	570 | 569 | 568	601 | 600	625 | 624 | 623	657 | 656 | 655
Emäputken pituus (mm)	95	105	120	135
Emäputken kulma	63,1° | 63,5° | 63,9°	63,5° | 63,9°	63,1° | 63,5° | 63,9°	63,1° | 63,5° | 63,
Akseliväli (mm)	1226 | 1226 | 1227	1261 | 1261	1287 | 1288 | 1288	1323 | 1323 | 132
Takahaarukan alaputken pituus (mm)	450 | 450 | 450	450 | 450	450 | 450 | 450	450 | 450 | 450
Stack-mitta (mm)	647 | 645 | 642	654 | 651	669 | 667 | 665	683 | 680 | 678
Reach-mitta (mm)	426 | 430 | 435	460 | 465	476 | 480 | 485	505 | 510 | 514
Kammen pituus (mm)	155	155	155	155

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.