REIGN ADVANCED E+ 2



SPECIFICATIES

E+ SYSTEM	
MOTOR	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
BEDIENINGSUNIT	Giant RideControl Ergo 4
DISPLAY	Giant RideControl Go Lux
ACCU	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
LADER	Giant EnergyPak 4A Charger, 48V
FRAME	
FRAME	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VOORVORK	RockShox Zeb select, 29", 180mm travel, Delta RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
DEMPER	RockShox SuperDeluxe Select, RT, 205x65mm, custom tuned, 30% sag recommended
ONDERDELEN	
STUUR	Giant Contact TR35, 35mm rize, Up: 5º Back: 9º, 35x800mm
HANDVATTEN	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
STUURPEN	Giant Contact SL 35, 40 mm
ZADELPEN	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
ZADEL	Giant Romero, neutral
AFMONTAGE	
SHIFTERS	Shimano Deore, 12-speed
ACHTERDERAILLEUR	Shimano Deore, RD-7200,12-speed Shadow+
REMMEN	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F/R]
REMHENDELS	TRP EVO Comp
CASSETTE	Shimano Deore, HyperGlide+, 12-speed, 11-51T
AANDRIJVING	Shimano Deore, 12-speed
CRANKSET	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

WIELSET	
VELGEN	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
NAVEN	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
SPAKEN	Sapim Race [F] E-Lite [R], e-bike optimized
BANDEN	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
EXTRA'S	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORES	
VERLICHTING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

Adviesprijs: € 6.999,00

GEOMETRIE

FRAME	**S**	**M**	**L**	**XL**
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Zitbuis Hoek	77,1° | 77,5° | 77,9°	77,5° | 77,9°	77,1° | 77,5° | 77,9°	77,1° | 77,5° | 77,9°
Frame Lengte (horizontaal) (mm)	570 | 569 | 568	601 | 600	625 | 624 | 623	657 | 656 | 655
Balhoofdbuis Lengte (mm)	95	105	120	135
Balhoofdbuis Hoek	63,1° | 63,5° | 63,9°	63,5° | 63,9°	63,1° | 63,5° | 63,9°	63,1° | 63,5° | 63,9°
Wielbasis (mm)	1226 | 1226 | 1227	1261 | 1261	1287 | 1288 | 1288	1323 | 1323 | 1324
Liggende achtervork lengte (mm)	450 | 450 | 450	450 | 450	450 | 450 | 450	450 | 450 | 450
Stack (mm)	647 | 645 | 642	654 | 651	669 | 667 | 665	683 | 680 | 678
Reach (mm)	426 | 430 | 435	460 | 465	476 | 480 | 485	505 | 510 | 514
Cranklengte (mm)	155	155	155	155

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.