

REIGN ADVANCED E+ 2



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X, 100Nm, 48V 800W max power, 400% max support ratio
STEUEREINHEIT	Giant RideControl Ergo 4
DISPLAY	Giant RideControl Go Lux
AKKU	Giant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
CHARGER	Giant EnergyPak 4A Charger, 48V
RAHMEN	
RAHMEN	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
GABEL	RockShox Zeb select, 29", 180mm travel, Delta RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
DÄMPFER	RockShox SuperDeluxe Select, RT, 205x65mm, custom tuned, 30% sag recommended
KOMPONENTEN	
LENKER	Giant Contact TR35, 35mm rise, Up: 5° Back: 9°, 35x800mm
GRIFFE	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
VORBAU	Giant Contact SL 35, 40 mm
SATTELSTÜTZE	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SATTEL	Giant Romero, neutral
ANTRIEB	
SCHALTHEBEL	Shimano Deore, 12-speed
SCHALTWERK	Shimano Deore, RD-7200, 12-speed Shadow+
BREMSSEN	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F/R]
BREMSHEBEL	TRP EVO Comp
KASSETTE	Shimano Deore, HyperGlide+, 12-speed, 11-51T
KETTE	Shimano Deore, 12-speed
KURBEL	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

LAUFRÄDER	
FELGEN	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
NABE	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
SPEICHEN	Sapim Race [F] E-Lite [R], e-bike optimized
REIFEN	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
EXTRAS	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
BELEUCHTUNG	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

GEOMETRIEDATEN

RAHMEN	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sitzrohrwinkel	77.1°	77.5°	77.9°	77.5°	77.9°	77.1°	77.5°	77.9°
Oberrohrlänge (mm)	570	569	568	601	600	625	624	623
Steuerrohr-Länge (mm)	95		105		120		135	
Steuerrohr-Winkel	63.1°	63.5°	63.9°	63.5°	63.9°	63.1°	63.5°	63.9°
Radstand (mm)	1226	1226	1227	1261	1261	1287	1288	1288
Kettenstreben-Länge (mm)	450	450	450	450	450	450	450	450
Stack (mm)	647	645	642	654	651	669	667	665
Reach (mm)	426	430	435	460	465	476	480	485
Kurbellänge (mm)	155		155		155		155	

Spezifikations-, Preis- und Farbänderungen vorbehalten.