

# REIGN ADVANCED E+ 2

**GIANT**



## TECHNIQUES

TECHNOLOGIE HYBRID	
<b>MOTEUR</b>	Giant SyncDrive Pro3, 48v, 90Nm, 800W max power, 400% max support ratio
<b>COMMANDE</b>	Giant RideControl Ergo 4
<b>ECRAN</b>	Giant RideControl GO Lux
<b>BATTERIE</b>	Giant EnergyPak Smart 560Wh, integrated, 48V
<b>ENERGYPAK PLUS COMPATIBLES</b>	Giant EnergyPak Plus 280 range extender compatible
<b>CHARGEUR</b>	Giant EnergyPak smart charger 4A, 48V
<b>CONNECTIVITÉ</b>	Tire Checker Aegis, E-Lock, FindMyBike
CADRE	
<b>TAILLES</b>	S, M, L, XL
<b>COLORIS</b>	Moon Dust
<b>CADRE</b>	Advanced-grade composite frame, Advanced forged composite upper rocker and internal link, 170mm Maestro suspension system
<b>FOURCHE</b>	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
<b>AMORTISSEUR</b>	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
COMPOSANTS	
<b>CINTRE</b>	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
<b>POIGNÉES</b>	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
<b>POTENCE</b>	Giant Contact SL 35
<b>TIGE DE SELLE</b>	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170, L/XL: 170-200) MMX remote
<b>SELLE</b>	Giant Romero, Neutral
DÉRAILLEUR	
<b>MANETTES</b>	Shimano Deore
<b>DÉRAILLEUR ARRIÈRE</b>	Shimano Deore, 12-speed shadow+
<b>FREINS</b>	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
<b>LEVIERS DE FREIN</b>	Shimano SLX
<b>CASSETTE</b>	Shimano Deore, 10-51T, 12-speed
<b>CHAÎNE</b>	Shimano Deore 12-speed
<b>PÉDALIER</b>	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

ROUES	
<b>JANTES</b>	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
<b>MOYEUX</b>	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
<b>RAYONS</b>	Sapim Race [F] E-Lite [R], e-bike optimized
<b>PNEUS</b>	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
<b>EXTRAS</b>	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
<b>ECLAIRAGE</b>	Kit d'éclairage avant et arrière à piles (éclairages e-bike Recon disponible et directement connectable)

**Prix Public Conseillé: 7 500,00 €**

## GÉOMÉTRIE

CADRE	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Longueur de tube de selle (mm)	400	425	450	475						
Seat Post Insertion Depth (mm)	235	260	285	310						
Angle de tube de selle	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°
Longueur du tube supérieur (mm)	570	569	568	602	601	600	625	624	623	657
Longueur du tube de direction (mm)	95	105	120	135						
Angle du tube de direction	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°
Déport de fourche (mm)	44	44	44	44						
Trail (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3
Empattement (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323
Longueur des bases (mm)	450	450	450	450	450	450	450	450	450	450
Drop du boîtier de pédalier (mm)	10	5	10	5	10	5	10	5	10	5
Stack (mm)	647	645	642	656	654	651	669	667	665	683
Reach (mm)	426	430	435	456	460	465	476	480	485	505
Largeur de cintre (mm)	800	800	800	800						
Longueur de potence (mm)	40	40	40	40						
Longueur des manivelles (mm)	160	160	160	160						
Diamètre des roues	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" /

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).  
GIANT France se réserve le droit de modifier les spécifications sans préavis.