



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Ergo 4
PRIKAZ	Giant RideControl GO Lux
BATERIJA	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
OKVIR	
VELIČINE	S, M, L, XL
BOJE	Moon Dust
OKVIR	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VILICA	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
AMORTIZER	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMPONENTE	
VOLAN	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
LULA VOLANA	Giant Contact SL 35
CIJEV SJEDALA	Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote
SJEDALO	Giant Romero, Neutral
POGON	
RUČICE MJENJAČA	Shimano Deore
STRAŽNJI MJENJAČ	Shimano Deore, 12-speed shadow+
KOČNICE	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
RUČICE KOČNICA	Shimano SLX
KAZETA	Shimano Deore, 10-51T, 12-speed
LANAC	Shimano Deore 12-speed
POGON	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

KOTAČI	
OBRUČI	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
NABE	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
ŽBICE	Sapim Race [F] E-Lite [R], e-bike optimized
GUME	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
DODACI	Aegis Tire Checker
DODACI	
SVJETLA	Optional: - Giant Recon series e-bike lights available and direct connectable

GEOMETRIJA

OKVIR	S			M		
	LOW	MID	HIGH	LOW	MID	HIGH
Dužina cijevi sjedala (mm)	400			425		
Seat Post Insertion Depth (mm)	235			260		
Kut cijevi sjedala	77,1° 77,5° 77,9°			77,1° 77,5° 77,9°		
Dužina gornje cijevi (mm)	570 569 568			602 601 600		
Dužina prednje cijevi (mm)	95			105		
Kut vilice	63,1° 63,5° 63,9°			63,1° 63,5° 63,9°		
Zakrivljenost vilice (offset) (mm)	44			44		
Staza (mm)	133,3 130,3 127,4			133,3 130,3 127,4		
Međuosovinski razmak kotača (mm)	1226 1226 1227			1261 1261 1261		
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	450 450 450			450 450 450		
Položaj osovine pogona (mm)	10 5			10 5		
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	647 645 642			656 654 651		
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	426 430 435			456 460 465		
Širina volana (mm)	800			800		
Dužina lule volana (mm)	40			40		
Dužina poluge pedale (mm)	160			160		
Veličina kotača	R27.5" / F29"			R27.5" / F29"		

Sve navedene specifikacije podložne su promjeni bez prethodne najave.