

REIGN ADVANCED E+ 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
COMANDO	Giant RideControl Ergo 4
DISPLAY	Giant RideControl GO Lux
BATTERIA	Giant EnergyPak Smart 560Wh, integrated, 48V
CARICATORE	Giant EnergyPak smart charger 4A, 48V
CONNETTIVITÀ	Aegis Tire Checker included in RideControl display
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Moon Dust
TELAIO	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
FORCELLA	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
AMMORTIZZATORE	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
MANOPOLE	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
ATTACCO MANUBRIO	Giant Contact SL 35
REGGISELLA	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170,L/XL: 170-200) MMX remote
SELLA	Giant Romero, Neutral
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore
DERAGLIATORE POSTERIORE	Shimano Deore, 12-speed shadow+
FRENI	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
COMANDI FRENO	Shimano SLX
PACCO PIGNONI	Shimano Deore, 10-51T, 12-speed
CATENA	Shimano Deore 12-speed
GUARNITURA	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

RUOTE	
CERCHI	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
MOZZI	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
RAGGI	Sapim Race [F] E-Lite [R], e-bike optimized
COPERTONI	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRA	Aegis Tire Checker
ACCESSORI	
ILLUMINAZIONE	Optional: - Giant Recon series e-bike lights available and direct connectable

Prezzo: 6.599,00 €

GEOMETRIA

TELAIO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Lunghezza Tubo Sella (mm)	400			425			450			475
Profondità inserimento reggisella (mm)	235			260			285			310
Angolo Tubo Sella	77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1°
Lunghezza Tubo Orizzontale (mm)	570 569 568			602 601 600			625 624 623			657
Lunghezza Tubo Sterzo (mm)	95			105			120			135
Angolo Sterzo	63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1°
Rake Forcella (mm)	44			44			44			44
Avancorsa (mm)	133,3 130,3 127,4			133,3 130,3 127,4			133,3 130,3 127,4			133,3
Interasse (mm)	1226 1226 1227			1261 1261 1261			1287 1288 1288			1323
Lunghezza Carro Posteriore (mm)	450 450 450			450 450 450			450 450 450			450
Drop Movimento Centrale (mm)	10 5			10 5			10 5			10 5
Stack (mm)	647 645 642			656 654 651			669 667 665			683
Reach (mm)	426 430 435			456 460 465			476 480 485			505
Larghezza Manubrio c/c (mm)	800			800			800			800
Lunghezza Attacco Manubrio (mm)	40			40			40			40
Lunghezza Pedivella (mm)	160			160			160			160
Dimensione Ruote	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.