

REIGN ADVANCED E+ 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
COMANDO	Giant RideControl Ergo 4
DISPLAY	Giant RideControl Go Lux
BATTERIA	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
CARICATORE	Giant EnergyPak 4A Charger, 48V
TELAIO	
TELAIO	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
FORCELLA	RockShox Zeb select, 29", 180mm travel, Delta RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
AMMORTIZZATORE	RockShox SuperDeluxe Select, RT, 205x65mm, custom tuned, 30% sag recommended
COMPONENTISTICA	
MANUBRIO	Giant Contact TR35, 35mm rize, Up: 5° Back: 9°, 35x800mm
MANOPOLE	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
ATTACCO MANUBRIO	Giant Contact SL 35, 40 mm
REGGISELLA	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SELLA	Giant Romero, neutral
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore, 12-speed
DERAGLIATORE POSTERIORE	Shimano Deore, RD-7200,12-speed Shadow+
FRENI	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F/R]
COMANDI FRENO	TRP EVO Comp
PACCO PIGNONI	Shimano Deore, HyperGlide+, 12-speed, 11-51T
CATENA	Shimano Deore, 12-speed
GUARNITURA	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

RUOTE	
CERCHI	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
MOZZI	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
RAGGI	Sapim Race [F] E-Lite [R], e-bike optimized
COPERTONI	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
EXTRA	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
ILLUMINAZIONE	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITI	
LIMITE MASSIMO DI CARICO COMBINATO	156kg

Prezzo: 6.999,00 €

GEOMETRIA

TELAIO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Angolo Tubo Sella	77,1°	77,5°	77,9°	77,5°	77,9°	77,1°	77,5°	77,9°
Lunghezza Tubo Orizzontale (mm)	570	569	568	601	600	625	624	623
Lunghezza Tubo Sterzo (mm)	95			105		120		
Angolo Sterzo	63,1°	63,5°	63,9°	63,5°	63,9°	63,1°	63,5°	63,9°
Interasse (mm)	1226	1226	1227	1261	1261	1287	1288	1288
Lunghezza Carro Posteriore (mm)	450	450	450	450	450	450	450	450
Stack (mm)	647	645	642	654	651	669	667	665
Reach (mm)	426	430	435	460	465	476	480	485
Lunghezza Pedivella (mm)	155			155		155		

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.