

REIGN ADVANCED E+ 2



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo 4
DISPLAY	Giant RideControl GO Lux
ACCU	Giant EnergyPak Smart 560Wh, integrated, 48V
LADER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
FRAME	
MATEN	S, M, L, XL
KLEUREN	Moon Dust
FRAME	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VOORVORK	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
DEMPER	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
ONDERDELEN	
STUUR	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
HANDVATTEN	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
STUURPEN	Giant Contact SL 35
ZADELPEN	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170,L/XL: 170-200) MMX remote
ZADEL	Giant Romero, Neutral
AFMONTAGE	
SHIFTERS	Shimano Deore
ACHTERDERAILLEUR	Shimano Deore, 12-speed shadow+
REMMEN	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
REMHENDELS	Shimano SLX
CASSETTE	Shimano Deore, 10-51T, 12-speed
AANDRIJVING	Shimano Deore 12-speed
CRANKSET	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

WIELSET	
VELGEN	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
NAVEN	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
SPAKEN	Sapim Race [F] E-Lite [R], e-bike optimized
BANDEN	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRA'S	Aegis Tire Checker
ACCESSOIRES	
VERLICHTING	Optional: - Giant Recon series e-bike lights available and direct connectable

Adviesprijs: € 6.699,00

GEOMETRIE

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Zitbuis lengte (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	235			260			285			310		
Zitbuis hoek	77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°		
Frame Lengte (horizontaal) (mm)	570	569	568	602	601	600	625	624	623	657	656	655
Balhoofdbuis Lengte (mm)	95			105			120			135		
Balhoofdbuis Hoek	63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°		
Vork Sprong (mm)	44			44			44			44		
Naloop (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4
Wielbasis (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323	1323	1323
Liggende achtervork lengte (mm)	450	450	450	450	450	450	450	450	450	450	450	450
Bottom Bracket Drop (mm)	10 5			10 5			10 5			10 5		
Stack (mm)	647	645	642	656	654	651	669	667	665	683	680	678
Reach (mm)	426	430	435	456	460	465	476	480	485	505	510	515
Stuur breedte (mm)	800			800			800			800		
Stuurpen Lengte (mm)	40			40			40			40		
Cranklengte (mm)	160			160			160			160		
Wielmaat	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.