

REIGN ADVANCED E+ 2

GIANT



SPECS

Tecnologia Híbrida de Ciclismo	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Ergo 4
ECRÃ	Giant RideControl GO Lux
BATERIA	Giant EnergyPak Smart 560Wh, integrated, 48V
CARREGADOR	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
Quadro	
TAMANHOS	S, M, L, XL
CORES	Moon Dust
QUADRO	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
FORQUILHA	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
AMORTECEDORES	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
Componentes	
GUIADOR	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
PUNHOS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
AVANÇO	Giant Contact SL 35
ESPIÃO DE SELIM	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170,L/XL: 170-200) MMX remote
SELIM	Giant Romero, Neutral
Transmissão	
MANETES	Shimano Deore
DESVIADOR TRASEIRO	Shimano Deore, 12-speed shadow+
TRAVÕES	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
MANÍPULOS DOS TRAVÕES	Shimano SLX
CASSETTE	Shimano Deore, 10-51T, 12-speed
CORRENTE	Shimano Deore 12-speed
CONJUNTO PEDALEIRO	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

Rodas	
AROS	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
CUBOS	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
RAIOS	Sapim Race [F] E-Lite [R], e-bike optimized
PNEUS	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Aegis Tire Checker
Acessórios	
LUZES	Optional: - Giant Recon series e-bike lights available and direct connectable

Preço: 5 899,00 €

GEOMETRIA

Quadro	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Comprimento do tubo do assento (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	235			260			285			310
Ângulo do tubo do assento	77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1°
Comprimento do tubo superior (mm)	570 569 568			602 601 600			625 624 623			657
Comprimento do tubo principal (mm)	95			105			120			135
Ângulo do tubo principal	63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1°
Garfo ancinho (mm)	44			44			44			44
Trilha (mm)	133,3 130,3 127,4			133,3 130,3 127,4			133,3 130,3 127,4			133,3
distância entre eixos (mm)	1226 1226 1227			1261 1261 1261			1287 1288 1288			1323
Comprimento Chain Stay (mm)	450 450 450			450 450 450			450 450 450			450
Suporte inferior (mm)	10 5			10 5			10 5			10 5
Pilha (mm)	647 645 642			656 654 651			669 667 665			683
Alcançar (mm)	426 430 435			456 460 465			476 480 485			505
Largura do guidão (mm)	800			800			800			800
Comprimento da haste (mm)	40			40			40			40
Comprimento da Manivela (mm)	160			160			160			160
Tamanho da roda	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.