



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
OVLÁDAČ	Giant RideControl Ergo 4
OVLÁDACIA JEDNOTKA	Giant RideControl GO Lux
BATÉRIA	Giant EnergyPak Smart 560Wh, integrated, 48V
NABÍJAČKA	Giant EnergyPak smart charger 4A, 48V
KONEKTIVITA	Aegis Tire Checker included in RideControl display
RÁM	
VELKOSTI	S, M, L, XL
FARBY	Moon Dust
RÁM	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VIDLICA	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
TLMIČ	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMPONENTY	
RIADIDLÁ	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
GRIPY	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
PREDSTAVEC	Giant Contact SL 35
SEDLOVKA	Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote
SEDADLO	Giant Romero, Neutral
POHON	
RADENIE	Shimano Deore
PREHADZOVAČKA	Shimano Deore, 12-speed shadow+
BRZDY	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
BRZDOVÉ PÁKY	Shimano SLX
KAZETA	Shimano Deore, 10-51T, 12-speed
REŤAZ	Shimano Deore 12-speed
KLUKY	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

KOLESÁ	
RÁFIKY	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
NÁBOJE	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
ŠPICE	Sapim Race [F] E-Lite [R], e-bike optimized
PNEUMATIKY	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
DOPLNKY	Aegis Tire Checker
PRÍSLUŠENSTVO	
OSVETLENIE	Optional: - Giant Recon series e-bike lights available and direct connectable

Cena: 6 699 €

GEOMETRIA

RÁM	S	M	L
Dĺžka sedlovej trubky (mm)	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Hĺbka vloženia sedlovky (mm)	235	260	285
Uhol sedlovej trubky	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°
Dĺžka hornej rámovej trubky (mm)	570 569 568	602 601 600	625 624 623
Dĺžka hlavovej trubky (mm)	95	105	120
Uhol hlavovej trubky	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°
Offset vidlice (mm)	44	44	44
Trail (mm)	133,3 130,3 127,4	133,3 130,3 127,4	133,3 130,3 127,4
Rázvor (mm)	1226 1226 1227	1261 1261 1261	1287 1288 1288
Dĺžka zadnej stavby (mm)	450 450 450	450 450 450	450 450 450
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	10 5	10 5	10 5
Stack - výška riadenia (mm)	647 645 642	656 654 651	669 667 665
Reach (mm)	426 430 435	456 460 465	476 480 485
Šírka riaditok (mm)	800	800	800
Dĺžka predstavca (mm)	40	40	40
Dĺžka klúku (mm)	160	160	160
Rozmer kolies	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.