



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
TIPALO	Giant RideControl Ergo 4
PRIKAZOVALNIK	Giant RideControl GO Lux
BATERIJA	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Moon Dust
OKVIR	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VILICE	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
AMORTIZER	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMPONENTE	
KRMILO	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
OPORA KRMILA	Giant Contact SL 35
OPORA SEDEŽA	Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote
SEDEŽ	Giant Romero, Neutral
POGON	
PRESTAVNE ROČICE	Shimano Deore
ZADNJI MENJALNIK	Shimano Deore, 12-speed shadow+
ZAVORE	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
ZAVORNE ROČICE	Shimano SLX
VERIŽNIK	Shimano Deore, 10-51T, 12-speed
VERIGA	Shimano Deore 12-speed
GONILKE Z VERIŽNIKI	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

OBROČNIKI	
OBROČI	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
PESTA	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
NAPERE	Sapim Race [F] E-Lite [R], e-bike optimized
PLAŠČI	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
DODATKI	Aegis Tire Checker
DODATNA OPREMA	
SVETILA	Optional: - Giant Recon series e-bike lights available and direct connectable

GEOMETRIJA

OKVIR	S	M	L
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Dolžina sedežne cevi (mm)	400	425	450
Seat Post Insertion Depth (mm)	235	260	285
Kot sedežne cevi	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°
Top Tube Length (mm)	570 569 568	602 601 600	625 624 623
Višina glave okvirja (mm)	95	105	120
Krmilni kot	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°
Zamik vpetja osi (mm)	44	44	44
Trail (mm)	133,3 130,3 127,4	133,3 130,3 127,4	133,3 130,3 127,4
Medosna razdalja (mm)	1226 1226 1227	1261 1261 1261	1287 1288 1288
Dolžina cevi ob verigi (mm)	450 450 450	450 450 450	450 450 450
Bottom Bracket Drop (mm)	10 5	10 5	10 5
Oddaljenost zgornje cevi od gonilne osi (mm)	647 645 642	656 654 651	669 667 665
Doseg (mm)	426 430 435	456 460 465	476 480 485
Širina krmila (mm)	800	800	800
Dolžina opore krmila (mm)	40	40	40
Dolžina gonilke (mm)	160	160	160
Velikost obročnikov	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.