REIGN ADVANCED E+ 2



SPECS

E+ SYSTEM	
MOTOR	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
KONTROLLER	Giant RideControl Ergo 4
VISA	Giant RideControl Go Lux
BATTERI	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
LADDARE	Giant EnergyPak 4A Charger, 48V
RAM	
RAM	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
GAFFEL	RockShox Zeb select, 29", 180mm travel, Delta RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
BAKDÄMPARE	RockShox SuperDeluxe Select, RT, 205x65mm, custom tuned, 30% sag recommended
KOMPONENTER	
STYRE	Giant Contact TR35, 35mm rize, Up: 5º Back: 9º, 35x800mm
GREPPAR	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
STAM	Giant Contact SL 35, 40 mm
SADELSTOLPE	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SADEL	Giant Romero, neutral
DRIVLINA	
VÄXLAR	Shimano Deore, 12-speed
BAKVÄXEL	Shimano Deore, RD-7200,12-speed Shadow+
BROMSAR	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F/R]
BROMSSPAKAR	TRP EVO Comp
KASSETT	Shimano Deore, HyperGlide+, 12-speed, 11-51T
KEDJA	Shimano Deore, 12-speed
VEVPARTI	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

HJUL	
FÄLGAR	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
NAV	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
EKRAR	Sapim Race [F] E-Lite [R], e-bike optimized
DÄCK	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
EXTRAFUNKTIONER	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
TILLBEHÖR	
BELYSNING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
GRÄNSER	
COMBINED MAXIMUM LOAD LIMIT	156kg

Price: 82 000,00 kr

GEOMETRY

RAM	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Vinkel sadelrör	77,1° | 77,5° | 77,9°	77,5° | 77,9°	77,1° | 77,5° | 77,9°	77,1° | 77,5° | 77,9°
Topprörets längd (mm)	570 | 569 | 568	601 | 600	625 | 624 | 623	657 | 656 | 655
Styrhuvud Längd (mm)	95	105	120	135
Vinkel styrhuvud	63,1° | 63,5° | 63,9°	63,5° | 63,9°	63,1° | 63,5° | 63,9°	63,1° | 63,5° | 63,9°
Hjulbas (mm)	1226 | 1226 | 1227	1261 | 1261	1287 | 1288 | 1288	1323 | 1323 | 1324
Kedjestagslängd (mm)	450 | 450 | 450	450 | 450	450 | 450 | 450	450 | 450 | 450
Stack (mm)	647 | 645 | 642	654 | 651	669 | 667 | 665	683 | 680 | 678
Reach (mm)	426 | 430 | 435	460 | 465	476 | 480 | 485	505 | 510 | 514
Vevlängd (mm)	155	155	155	155

All specifications listed are subject to change without notice.