



СПЕЦИФІКАЦІЯ

ТЕХНОЛОГІЯ HYBRID CYCLING	
ДВИГУН	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
КОНТРОЛЕР	Giant RideControl Ergo 4
ДИСПЛЕЙ	Giant RideControl GO Lux
БАТАРЕЯ	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
РАМА	
РОЗМІР	S, M, L, XL
КОЛІР	Moon Dust
КОНСТРУКЦІЯ	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
ВИЛКА	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
АМОРТИЗАТОР ЗАДНІЙ	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
КОМПОНЕНТИ	
КЕРМО	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
РУКОЯТКИ / ОБМОТКА	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
ВИНОС КЕРМА	Giant Contact SL 35
ВИНОС СІДЛА	Giant Contact Switch adjustable dropper, 30,9mm (S:110–140, M:140–170, L/XL: 170–200) MMX remote
СІДЛО	Giant Romero, Neutral
ПРИВІД	
МАНЕТКИ	Shimano Deore
ПЕРЕМИКАЧ ЗАДНІЙ	Shimano Deore, 12-speed shadow+
ГАЛЬМА	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
ВАЖЕЛІ ГАЛЬМ	Shimano SLX
КАСЕТА	Shimano Deore, 10-51T, 12-speed
ЛАНЦЮГ	Shimano Deore 12-speed
СИСТЕМА ШАТУНІВ	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

КОЛЕСА	
ОБОДИ	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
ВТУЛКИ	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
СПИЦІ	Sapim Race [F] E-Lite [R], e-bike optimized
ШИНИ	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
ДОДАТКОВО	Aegis Tire Checker
АКСЕСУАРИ	
ОСВІТЛЕННЯ	Optional: - Giant Recon series e-bike lights available and direct connectable

ГЕОМЕТРІЯ

РАМА	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Довжина підсідельної труби (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Нахил підсідельної труби	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°
Довжина верхньої труби (mm)	570 569 568	602 601 600	625 624 623	657 656 655
Висота кермової труби (mm)	95	105	120	135
Нахил кермової труби	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°
Виліт вилки (mm)	44	44	44	44
Шлях вилки (mm)	133,3 130,3 127,4	133,3 130,3 127,4	133,3 130,3 127,4	133,3 130,3 127,4
Колісна база (mm)	1226 1226 1227	1261 1261 1261	1287 1288 1288	1323 1323 1323
Довжина нижнього пір'я рами (mm)	450 450 450	450 450 450	450 450 450	450 450 450
Провисання каретки (mm)	10 5	10 5	10 5	10 5
Ефективна висота (mm)	647 645 642	656 654 651	669 667 665	683 681 679
Ефективна довжина (mm)	426 430 435	456 460 465	476 480 485	505 509 514
Ширина керма (mm)	800	800	800	800
Довжина виносу (mm)	40	40	40	40
Довжина шатунів (mm)	160	160	160	160
Розмір коліс	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"

Giant залишає за собою право змінювати специфікації без попереднього повідомлення.