

REIGN ADVANCED

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Luminous Lagoon
FRAME	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, integrated downtube storage, 55mm Chainline
FORK	RockShox Zeb Ultimate Charger 3.2, 170mm,15x110mm Maxle Stealth thru-axle
SHOCK	RockShox Vivid Ultimate RCT2, 2 position, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm rise
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
REAR DERAILLEUR	SRAM GX Eagle Transmission AXS
BRAKES	TRP EVO Pro, hydraulic, TRP 2.3mm rotors [F]203mm, [R]180mm
BRAKE LEVERS	TRP EVO Pro
CASSETTE	SRAM XS-1275, Transmission, 10x52
CHAIN	SRAM GX Transmission
CRANKSET	SRAM GX Transmission, 32t, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRA Hookless Tubeless ready Alloy Fr: 29", Rr: 27.5" 30mm inner width
HUBS	[F] Giant TRA MTB Alloy Hub, 6 Bolt, 28H [R] Giant TRX MTB Alloy Hub, SRAM XD Drive Body Pawl Driver (Pawl 36x2 T), 28H
SPOKES	Sapim Laser
TYRES	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, MaxxTerra, DD, TR tubeless
EXTRAS	Tubeless prepared, MRP AMG chain guide
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	36t

Price: \$8,999.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	77.5° 77.8° 78.2°			77.5° 77.8° 78.2°			76.5° 76.9° 77.2°			76.5° 76.9° 77.2°		
Top Tube Length (mm)	558 557 556			589 588 587			622 621 621			654 653 653		
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	62.7° 63.0° 63.4°			62.7° 63.0° 63.4°			62.7° 63.1° 63.4°			62.7° 63.1° 63.4°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	147 144 141			147 144 141			147 144 141			147 144 141		
Wheelbase (mm)	1214 1213 1212			1246 1245 1244			1271 1270 1269			1304 1303 1302		
Chain Stay Length (mm)	445 443 442			445 443 442			445 443 442			445 443 442		
Bottom Bracket Drop (mm)	29 24 19			29 24 19			29 24 19			29 24 19		
Stack (mm)	633 630 627			638 635 632			647 644 641			652 649 646		
Reach (mm)	418 421 426			448 452 456			468 471 476			499 503 507		
Stand Over Height (mm)	714 718 723			733 738 742			746 750 755			762 766 771		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.