



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Luminous Lagoon/Chrome
CUADRO	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
HORQUILLA	RockShox Zeb Ultimate, Charger 3.2 RC2 damper, 170mm, 15x110, Maxle Stealth, Debonair
AMORTIGUADOR	RockShox Vivid Ultimate, RCT2, adjustable hydraulic bottom out, trunnion mount, 205/65 S:425#, M:425#, L:450#, XL: 475#
COMPONENTES	
MANILLAR	Giant Contact TR35, 800x35mm, 35mm rise
PUÑOS	Giant Tactal Pro Single
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIJA DE SILLÍN	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SILLÍN	Giant Romero SL
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Pod, 1x12
CAMBIO TRASERO	SRAM GX AXS Transmission
FRENOS	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
PALANCAS DE FRENOS	TRP EVO Pro
CASETTE	SRAM GX Eagle Transmission, 10x52
CADENA	SRAM GX Eagle Transmission
JGO. PLATOS Y BIELAS	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
BUJES	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
RADIOS	Sapim, 28, straight pull, DBL Technology
CUBIERTAS	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Precio: 6.999,00 €

GEOMETRÍA

CUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Longitud del tubo del sillín (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	262			287			312			337
Ángulo del tubo del sillín	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°
Longitud del tubo superior (mm) (mm)	558	557	556	589	588	587	622	621	621	654
Longitud del tubo de dirección (mm) (mm)	100			105			115			120
Ángulo del tubo de dirección	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°
Inclinación de la horquilla (mm)	44			44			44			44
Trail (mm) (mm)	147	144	141	147	144	141	147	144	141	147
Distancia entre ejes (mm) (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304
Longitud de la vaina (mm) (mm)	445	443	442	445	443	442	445	443	442	445
Caída del eje de pedalier (mm) (mm)	29	24	19	29	24	19	29	24	19	29
Stack (mm) (mm)	633	630	627	638	635	632	647	644	641	652
Reach (mm) (mm)	418	421	426	448	452	456	468	471	476	499
Altura del suelo al tubo (mm) (mm)	714	718	723	733	738	742	746	750	755	762
Ancho del manillar (mm) (mm)	800			800			800			800
Longitud de la potencia (mm) (mm)	40			40			40			40
Longitud de las bielas (mm) (mm)	165			170			170			170
Tamaño de ruedas	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F]

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.