



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
RAHMEN	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
DÄMPFER	Fox Float DHX2 Factory 2 position adjust, Trunnion mount, 205x62,5, custom tuned for Giant, recommended sag 30%

LAUFRÄDER	
EXTRAS	2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector
LIMITS	
MAX CHAINRING SIZE	36T

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Sitzrohrwinkel	78.3°	78.7°	79.0°	78.3°	78.7°	79.0°	77.3°	77.7°	78.0°	77.3°	77.7°	78.0°
Oberrohrlänge (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Steuerrohr-Länge (mm)	100			105			115			120		
Steuerrohr-Winkel	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Radstand (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Kettenstreben-Länge (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Tretlager-Höhe (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Überstandshöhe (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Lenkerbreite (mm)	800			800			800			800		
Vorbaulänge (mm)	40			40			40			40		
Kurbellänge (mm)	165			170			170			170		
Radgrösse	29"			29"			29"			29"		

Spezifikations-, Preis- und Farbänderungen vorbehalten.