

REIGN ADVANCED PRO 0

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Gloss Messier/Matte Carbon
CUADRO	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
HORQUILLA	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIGUADOR	Fox DHX2 Factory, coil, 205/62.5, custom tuned for Giant S:425#, M:425#, L:450#, XL: 475#
COMPONENTES	
MANILLAR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
PUÑOS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIJA DE SILLÍN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SILLÍN	Giant Romero SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM XX1 Eagle AXS Eagle
FRENOS	Shimano XTR M-9120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
PALANCAS DE FRENOS	Shimano XTR BL-M9120
CASSETTE	SRAM X01 Eagle, 10x52
CADENA	SRAM X01 Eagle
JGO. PLATOS Y BIELAS	SRAM XX1 Eagle, 34t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	ZIPP 3ZERO MOTO with TyreWiz
BUJES	ZIPP 3ZERO MOTO
RADIOS	ZIPP 3ZERO MOTO
CUBIERTAS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG chain guide, 3M tailgate protector

Precio: 11.999,00 €

GEOMETRÍA

CUADRO	S	M	L	XL
Longitud del tubo del sillín (mm)	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW
Ángulo del tubo del sillín	78,3° 78,7° 79,0°	78,3° 78,7° 79,0°	77,3° 77,7° 78,0°	77,3°
Longitud del tubo superior (mm) (mm)	556 555 555	587 586 585	620 620 619	652
Longitud del tubo de dirección (mm) (mm)	100	105	115	120
Ángulo del tubo de dirección	63,5° 63,9° 64,2°	63,5° 63,9° 64,2°	63,5° 63,9° 64,2°	63,5°
Inclinación de la horquilla (mm)	44	44	44	44
Trail (mm) (mm)	140 138 135	140 138 135	140 138 135	140
Distancia entre ejes (mm) (mm)	1214 1213 1212	1246 1245 1244	1271 1270 1269	1304
Longitud de la vaina (mm) (mm)	445 443 442	445 443 442	445 443 442	445
Caída del eje de pedalier (mm) (mm)	35 30 25	35 30 25	35 30 25	35 30 25
Stack (mm) (mm)	627 624 622	632 629 626	641 638 635	645
Reach (mm) (mm)	426 430 434	456 460 464	476 480 484	506
Altura del suelo al tubo (mm) (mm)	720 724 729	735 739 744	751 756 760	746
Ancho del manillar (mm) (mm)	800	800	800	800
Longitud de la potencia (mm) (mm)	40	40	40	40
Longitud de las bielas (mm) (mm)	165	170	170	170
Tamaño de ruedas	29"	29"	29"	29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.