

REIGN ADVANCED PRO 0

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Gloss Messier/Matte Carbon
CUADRO	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
TIJERA	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIGUADOR	Fox DHX2 Factory, coil, 205/62.5, custom tuned for Giant S:425#, M:425#, L:450#, XL: 475#
COMPONENTES	
MANUBRIO	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
POSTE DE ASIENTO	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
ASIENTO	Giant Romero SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM XX1 Eagle AXS Eagle
FRENOS	Shimano XTR M-9120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
PALANCAS DE FRENOS	Shimano XTR BL-M9120
CASSETTE	SRAM X01 Eagle, 10x52
CADENA	SRAM X01 Eagle
MULTIPLICACIÓN	SRAM XX1 Eagle, 34t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	ZIPP 3ZERO MOTO with TyreWiz
MAZAS	ZIPP 3ZERO MOTO
RAYOS	ZIPP 3ZERO MOTO
NEUMÁTICOS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG chain guide, 3M tailgate protector

Precio: \$279,900.00

GEOMETRÍA

CUADRO	S			M			L			L
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	
Longitud de la Base del Poste de Asiento (mm)	400			425			450			4
Ángulo de la Base del Poste de Asiento	78.3°	78.7°	79.0°	78.3°	78.7°	79.0°	77.3°	77.7°	78.0°	7
Longitud del Tubo Superior (mm)	556	555	555	587	586	585	620	620	619	6
Longitud del Telescopio (mm)	100			105			115			1
Ángulo del Telescopio	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	6
Rake (mm)	44			44			44			4
Trail (mm)	140	138	135	140	138	135	140	138	135	1
Distancia entre Ejes (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1
Longitud de Vaina Inferior (mm)	445	443	442	445	443	442	445	443	442	4
Caída del Eje de Centro (mm)	35	30	25	35	30	25	35	30	25	3
Stack (mm)	627	624	622	632	629	626	641	638	635	6
Reach (mm)	426	430	434	456	460	464	476	480	484	5
Altura del Tubo Superior al Suelo (mm)	720	724	729	735	739	744	751	756	760	7
Ancho del Manubrio (mm)	800			800			800			8
Longitud de la Potencia (mm)	40			40			40			4
Longitud de la Biela (mm)	165			170			170			1
Tamaño de las Ruedas	29"			29"			29"			2

Todas las especificaciones están sujetas a cambios sin previo aviso.