

REIGN ADVANCED PRO 0



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Gloss Messier/Matte Carbon
RUNKO	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
HAARUKKA	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
ISKUNVAIMENNIN	Fox DHX2 Factory, coil, 205/62.5, custom tuned for Giant S:425#, M:425#, L:450#, XL: 475#
KOMONENTIT	
OHJAUSTANKO	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPIT	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OHJAINKANNATIN	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SATULATOLPPA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SATULA	Giant Romero SL
POLKIMET	N/A
VOIMANSIIRTO	
VAIHDEVIPU	SRAM AXS, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	SRAM XX1 Eagle AXS Eagle
JARRUT	Shimano XTR M-9120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
JARRUKAHVAT	Shimano XTR BL-M9120
RATASPAKKA	SRAM X01 Eagle, 10x52
KETJUT	SRAM X01 Eagle
KAMPISARJA	SRAM XX1 Eagle, 34t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	ZIPPP 3ZERO MOTO with TyreWiz
NAVAT	ZIPPP 3ZERO MOTO
PINNAT	ZIPPP 3ZERO MOTO
RENKAAT	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
LISÄTIEDOT	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG chain guide, 3M tailgate protector

Suositusinta: 12 449,00 €

GEOMETRIA

RUNKO	M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Satulaputken pituus (mm)	425			450			475		
Satulaputken kulma	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	78,0°
Vaakaputken pituus (mm)	587	586	585	620	620	619	652	652	651
Emäputken pituus (mm)	105			115			120		
Emäputken kulma	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°
Haarukan offset (mm)	44			44			44		
Trail-mitta (mm)	140	138	135	140	138	135	140	138	135
Akseliväli (mm)	1246	1245	1244	1271	1270	1269	1304	1303	1302
Takahaarukan alaputken pituus (mm)	445	443	442	445	443	442	445	443	442
Keskiön pudotus (mm)	35	30	25	35	30	25	35	30	25
Stack-mitta (mm)	632	629	626	641	638	635	645	642	639
Reach-mitta (mm)	456	460	464	476	480	484	506	510	514
Standover-mitta (mm)	735	739	744	751	756	760	746	751	756
Ohjaustangon leveys (mm)	800			800			800		
Ohjainkannattimen pituus (mm)	40			40			40		
Kammen pituus (mm)	170			170			170		
Rengaskoko	29"			29"			29"		

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.