

REIGN ADVANCED PRO 0

GIANT



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Gloss Messier/Matte Carbon
RAM	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
GAFFEL	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
BAKDÄMPARE	Fox DHX2 Factory, coil, 205/62.5, custom tuned for Giant S:425#, M:425#, L:450#, XL: 475#
KOMPONENTER	
STYRE	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GREPPAR	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STAM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SADELSTOLPE	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SADEL	Giant Romero SL
PEDALER	N/A
DRIVLINÄ	
VÄXLAR	SRAM AXS, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM XX1 Eagle AXS Eagle
BROMSAR	Shimano XTR M-9120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BROMSSPAKAR	Shimano XTR BL-M9120
KASSETT	SRAM X01 Eagle, 10x52
KEDJA	SRAM X01 Eagle
VEVPARTI	SRAM XX1 Eagle, 34t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	ZIPPP 3ZERO MOTO with TyreWiz
NAV	ZIPPP 3ZERO MOTO
EKRAR	ZIPPP 3ZERO MOTO
DÄCK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG chain guide, 3M tailgate protector

Price: 141 290,00 kr

GEOMETRY

RAM	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Längd sadelrör (mm)	425	450	475
Vinkel sadelrör	78,3° 78,7° 79,0°	77,3° 77,7° 78,0°	77,3° 77,7° 78,0°
Topprörets längd (mm)	587 586 585	620 620 619	652 652 651
Styrhuvud Längd (mm)	105	115	120
Vinkel styrhuvud	63,5° 63,9° 64,2°	63,5° 63,9° 64,2°	63,5° 63,9° 64,2°
Gaffelvinkel (mm)	44	44	44
Spår (mm)	140 138 135	140 138 135	140 138 135
Hjulbas (mm)	1246 1245 1244	1271 1270 1269	1304 1303 1302
Kedjestagslängd (mm)	445 443 442	445 443 442	445 443 442
Nedre fäste Drop (mm)	35 30 25	35 30 25	35 30 25
Stack (mm)	632 629 626	641 638 635	645 642 639
Reach (mm)	456 460 464	476 480 484	506 510 514
Stå över höjden (mm)	735 739 744	751 756 760	746 751 756
Styrets bredd (mm)	800	800	800
Stamlängd (mm)	40	40	40
Vevlängd (mm)	170	170	170
Hjulstorlek	29"	29"	29"

All specifications listed are subject to change without notice.