REIGN ADVANCED PRO 1

SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Gloss Black Diamond/Matte Carbon
FRAME	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FORK	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
SHOCK	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SADDLE	Giant Romero SL
DRIVETRAIN	
SHIFTERS	SRAM GX Eagle, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle
BRAKES	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BRAKE LEVERS	Shimano SLX BL-M7100
CASSETTE	SRAM GX XG-1275 Eagle, 10x52
CHAIN	SRAM GX Eagle
CRANKSET	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRY

FRAME	S	M	L	XL
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	78,3° | 78,7° | 79,0°	78,3° | 78,7° | 79,0°	77,3° | 77,7° | 78,0°	77,3° | 77,7° | 78,0°
Top Tube Length (mm)	556 | 555 | 555	587 | 586 | 585	620 | 620 | 619	652 | 652 | 651
Head Tube Length (mm)	100	105	115	120
Head Tube Angle	63,5° | 63,9° | 64,2°	63,5° | 63,9° | 64,2°	63,5° | 63,9° | 64,2°	63,5° | 63,9° | 64,2°
Fork Rake (mm)	44	44	44	44
Trail (mm)	140 | 138 | 135	140 | 138 | 135	140 | 138 | 135	140 | 138 | 135
Wheelbase (mm)	1214 | 1213 | 1212	1246 | 1245 | 1244	1271 | 1270 | 1269	1304 | 1303 | 1302
Chain Stay Length (mm)	445 | 443 | 442	445 | 443 | 442	445 | 443 | 442	445 | 443 | 442
Bottom Bracket Drop (mm)	35 | 30 | 25	35 | 30 | 25	35 | 30 | 25	35 | 30 | 25
Stack (mm)	627 | 624 | 622	632 | 629 | 626	641 | 638 | 635	645 | 642 | 639
Reach (mm)	426 | 430 | 434	456 | 460 | 464	476 | 480 | 484	506 | 510 | 514
Stand Over Height (mm)	720 | 724 | 729	735 | 739 | 744	751 | 756 | 760	746 | 751 | 756
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	40	40	40
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.