

REIGN ADVANCED PRO 1

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Gloss Black Diamond/Matte Carbon
RAMME	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FORGAFFEL	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
BAGDÆMPER	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
KOMPONENTER	
STYR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GREB / STYRBÅND	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
FREMPIND	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SADELPIND	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SADEL	Giant Romero SL
GEARGRUPPE	
SKIFTEGREB	SRAM GX Eagle, 1x12
FORSKIFTER	N/A
BAGSKIFTER	SRAM GX Eagle
BREMSE	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BREMSEGREB	Shimano SLX BL-M7100
KASSETTE	SRAM GX XG-1275 Eagle, 10x52
KÆDE	SRAM GX Eagle
KRANKSÆT	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
EGER	Sapim
DÆK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EKSTRA	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Pris: 53.999,00 kr.

GEOMETRI

RAMME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	H
Sadelrørslængde (mm)	400			425			450			475		
Sadelrørsvinkel	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	
Overrørslængde (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Kronrørslængde (mm)	100			105			115			120		
Kronrørsvinkel	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	
Forgaffel fremspring (rake) (mm)	44			44			44			44		
Sti (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Akselafstand (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Kædestagslængde (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Krankboks drop (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Skridthøjde (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Styrbredde (mm)	800			800			800			800		
Frempindslængde (mm)	40			40			40			40		
Pedalarmslængde (mm)	165			170			170			170		
Hjulstørrelse	29"			29"			29"			29"		

Alle de anførte specifikationer kan ændres uden varsel.