

REIGN ADVANCED PRO 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Gloss Black Diamond/Matte Carbon
RAHMEN	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
GABEL	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
DÄMPFER	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIFFE	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SATTELSTÜTZE	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SATTEL	Giant Romero SL
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle
BREMSEN	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BREMSHEBEL	Shimano SLX BL-M7100
KASSETTE	SRAM GX XG-1275 Eagle, 10x52
KETTE	SRAM GX Eagle
KURBEL	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPEICHEN	Sapim
REIFEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohlänge (mm)	400			425			450			475		
Sitzrohrwinkel	78.3°	78.7°	79.0°	78.3°	78.7°	79.0°	77.3°	77.7°	78.0°	77.3°	77.7°	78.0°
Oberrohrlänge (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Steuerrohr-Länge (mm)	100			105			115			120		
Steuerrohr-Winkel	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Radstand (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Kettenstreben-Länge (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Tretlager-Höhe (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Überstandshöhe (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Lenkerbreite (mm)	800			800			800			800		
Vorbaulänge (mm)	40			40			40			40		
Kurbellänge (mm)	165			170			170			170		
Radgrösse	29"			29"			29"			29"		

Spezifikations-, Preis- und Farbänderungen vorbehalten.