

REIGN ADVANCED PRO 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Gloss Black Diamond/Matte Carbon
FRAME	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FORK	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
SHOCK	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SADDLE	Giant Romero SL
DRIVETRAIN	
SHIFTERS	SRAM GX Eagle, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle
BRAKES	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BRAKE LEVERS	Shimano SLX BL-M7100
CASSETTE	SRAM GX XG-1275 Eagle, 10x52
CHAIN	SRAM GX Eagle
CRANKSET	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Price: ₹ 6,799.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Tube Angle	78.3° 78.7° 79.0°			78.3° 78.7° 79.0°			77.3° 77.7° 78.0°			77.3° 77.7° 78.0°		
Top Tube Length (mm)	556 555 555			587 586 585			620 620 619			652 652 651		
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	63.5° 63.9° 64.2°			63.5° 63.9° 64.2°			63.5° 63.9° 64.2°			63.5° 63.9° 64.2°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	140 138 135			140 138 135			140 138 135			140 138 135		
Wheelbase (mm)	1214 1213 1212			1246 1245 1244			1271 1270 1269			1304 1303 1302		
Chain Stay Length (mm)	445 443 442			445 443 442			445 443 442			445 443 442		
Bottom Bracket Drop (mm)	35 30 25			35 30 25			35 30 25			35 30 25		
Stack (mm)	627 624 622			632 629 626			641 638 635			645 642 639		
Reach (mm)	426 430 434			456 460 464			476 480 484			506 510 514		
Stand Over Height (mm)	720 724 729			735 739 744			751 756 760			746 751 756		
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29"			29"			29"			29"		

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.