

REIGN ADVANCED PRO 1

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Gloss Black Diamond/Matte Carbon
RUNKO	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
HAARUKKA	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
ISKUNVAIMENNIN	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
KOMONENTIT	
OHJAUSTANKO	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPIT	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OHJAINKANNATIN	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SATULATOLPPA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SATULA	Giant Romero SL
VOIMANSIIRTO	
VAIHDEVIPU	SRAM GX Eagle, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	SRAM GX Eagle
JARRUT	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
JARRUKAHVAT	Shimano SLX BL-M7100
RATASPAKKA	SRAM GX XG-1275 Eagle, 10x52
KETJUT	SRAM GX Eagle
KAMPISARJA	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NAVAT	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
PINNAT	Sapim
RENKAAT	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
LISÄTIEDOT	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Suositusinta: 7 259,00 €

GEOMETRIA

RUNKO	S			M			L			XL	
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID
Satulaputken pituus (mm)	400			425			450			475	
Satulaputken kulma	78,3° 78,7° 79,0°			78,3° 78,7° 79,0°			77,3° 77,7° 78,0°			77,3° 77,7° 78,0°	
Vaakaputken pituus (mm)	556	555	555	587	586	585	620	620	619	652	652
Emäputken pituus (mm)	100			105			115			120	
Emäputken kulma	63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°	
Haarukan offset (mm)	44			44			44			44	
Trail-mitta (mm)	140	138	135	140	138	135	140	138	135	140	138
Akseliväli (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303
Takahaarukan alaputken pituus (mm)	445	443	442	445	443	442	445	443	442	445	443
Keskion pudotus (mm)	35	30	25	35	30	25	35	30	25	35	30
Stack-mitta (mm)	627	624	622	632	629	626	641	638	635	645	642
Reach-mitta (mm)	426	430	434	456	460	464	476	480	484	506	510
Standover-mitta (mm)	720	724	729	735	739	744	751	756	760	746	751
Ohjaustangon leveys (mm)	800			800			800			800	
Ohjainkannattimen pituus (mm)	40			40			40			40	
Kammen pituus (mm)	165			170			170			170	
Rengaskoko	29"			29"			29"			29"	

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.