

REIGN ADVANCED PRO 1



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Gloss Black Diamond/Matte Carbon
CADRE	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FOURCHE	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTISSEUR	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIGE DE SELLE	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SELLE	Giant Romero SL
DÉRAILLEUR	
MANETTES DÉRAILLEUR	SRAM GX Eagle, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM GX Eagle
FREINS	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
LEVIERS DE FREIN	Shimano SLX BL-M7100
CASSETTE	SRAM GX XG-1275 Eagle, 10x52
CHAÎNE	SRAM GX Eagle
PÉDALIER	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
MOYEURS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAYONS	Sapim
PNEUS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Angle de tube de selle	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	78,0°
Longueur du tube supérieur (mm)	556	555	555	587	586	585	620	620	619	652	652	652
Longueur du tube de direction (mm)	100			105			115			120		
Angle du tube de direction	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°
Déport de fourche (mm)	44			44			44			44		
Chasse (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Empattement (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Longueur des bases (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Hauteur du boîtier de pédalier (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	640
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Hauteur d'enjambement (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			40			40		
Longueur des manivelles (mm)	165			170			170			170		
Diamètre des roues	29"			29"			29"			29"		

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.