

REIGN ADVANCED PRO 1



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Gloss Black Diamond/Matte Carbon
FRAME	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
VOORVORK	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
DEMPER	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
HANDVATTEN	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STUURPEN	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
ZADELPEEN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
ZADEL	Giant Romero SL
AFMONTAGE	
SHIFTERS	SRAM GX Eagle, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM GX Eagle
REMMEN	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
REMHENDELS	Shimano SLX BL-M7100
CASSETTE	SRAM GX XG-1275 Eagle, 10x52
AAANDRIJVING	SRAM GX Eagle
CRANKSET	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPAKEN	Sapim
BANDEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRA'S	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Adviesprijs: € 6.999,00

GEOMETRIE

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	H
Zitbuis lengte (mm)	400			425			450			475		
Zitbuis hoek	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	
Frame Lengte (horizontaal) (mm)	556	555	555	587	586	585	620	620	619	652	652	65
Balhoofdbuis Lengte (mm)	100			105			115			120		
Balhoofdbuis Hoek	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	
Vork Sprong (mm)	44			44			44			44		
Naloop (mm)	140	138	135	140	138	135	140	138	135	140	138	13
Wielbasis (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	
Liggende achtervork lengte (mm)	445	443	442	445	443	442	445	443	442	445	443	44
Bottom Bracket Drop (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	63
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	51
Stand Over Height (mm)	720	724	729	735	739	744	751	756	760	746	751	75
Stuur breedte (mm)	800			800			800			800		
Stuurpen Lengte (mm)	40			40			40			40		
Cranklengte (mm)	165			170			170			170		
Wielmaat	29"			29"			29"			29"		

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.