

REIGN ADVANCED PRO 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Gloss Black Diamond/Matte Carbon
OKVIR	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
VILICE	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SEDEŽ	Giant Romero SL
POGON	
PRESTAVNE ROČICE	SRAM GX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle
ZAVORE	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
ZAVORNE ROČICE	Shimano SLX BL-M7100
VERIŽNIK	SRAM GX XG-1275 Eagle, 10x52
VERIGA	SRAM GX Eagle
GONILKE Z VERIŽNIKI	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
NAPERE	Sapim
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRIJA

OKVIR	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LO
Dolžina sedežne cevi (mm)	400			425			450			475
Kot sedežne cevi	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,7°
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	652
Višina glave okvirja (mm)	100			105			115			120
Krmilni kot	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°
Zamik vpetja osi (mm)	44			44			44			44
Trail (mm)	140	138	135	140	138	135	140	138	135	140
Medosna razdalja (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1300
Dolžina cevi ob verigi (mm)	445	443	442	445	443	442	445	443	442	443
Bottom Bracket Drop (mm)	35	30	25	35	30	25	35	30	25	35
Oddaljenost zgornje cevi od gonilne osi (mm)	627	624	622	632	629	626	641	638	635	645
Doseg (mm)	426	430	434	456	460	464	476	480	484	508
Višina zgornje cevi (mm)	720	724	729	735	739	744	751	756	760	748
Širina krmila (mm)	800			800			800			800
Dolžina opore krmila (mm)	40			40			40			40
Dolžina gonilke (mm)	165			170			170			170
Velikost obročnikov	29"			29"			29"			29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.