

REIGN ADVANCED PRO 1

GIANT



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Gloss Black Diamond/Matte Carbon
RAM	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
GAFFEL	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
BAKDÄMPARE	Fox Float X2 Performance Elite, 205/62.5, custom tuned for Giant
KOMPONENTER	
STYRE	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GREPPAR	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STAM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SADELSTOLPE	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SADEL	Giant Romero SL
DRIVLINÄ	
VÄXLAR	SRAM GX Eagle, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM GX Eagle
BROMSAR	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BROMSSPAKAR	Shimano SLX BL-M7100
KASSETT	SRAM GX XG-1275 Eagle, 10x52
KEDJA	SRAM GX Eagle
VEVPARTI	SRAM GX, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
EKRAR	Sapim
DÄCK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Price: 82 390,00 kr

GEOMETRY

RAM	S				M				L				XL			
	LOW MID HIGH				LOW MID HIGH				LOW MID HIGH				LOW MID HIGH			
Längd sadelrör (mm)	400				425				450				475			
Vinkel sadelrör	78,3° 78,7° 79,0°				78,3° 78,7° 79,0°				77,3° 77,7° 78,0°				77,3° 77,7° 78,0°			
Topprörets längd (mm)	556 555 555				587 586 585				620 620 619				652 652 651			
Styrhuvud Längd (mm)	100				105				115				120			
Vinkel styrhuvud	63,5° 63,9° 64,2°				63,5° 63,9° 64,2°				63,5° 63,9° 64,2°				63,5° 63,9° 64,2°			
Gaffelvinkel (mm)	44				44				44				44			
Spår (mm)	140 138 135				140 138 135				140 138 135				140 138 135			
Hjulbas (mm)	1214 1213 1212				1246 1245 1244				1271 1270 1269				1304 1303 1302			
Kedjestagslängd (mm)	445 443 442				445 443 442				445 443 442				445 443 442			
Nedre fäste Drop (mm)	35 30 25				35 30 25				35 30 25				35 30 25			
Stack (mm)	627 624 622				632 629 626				641 638 635				645 642 639			
Reach (mm)	426 430 434				456 460 464				476 480 484				506 510 514			
Stå över höjden (mm)	720 724 729				735 739 744				751 756 760				746 751 756			
Styrets bredd (mm)	800				800				800				800			
Stamlängd (mm)	40				40				40				40			
Vevlängd (mm)	165				170				170				170			
Hjulstorlek	29"				29"				29"				29"			

All specifications listed are subject to change without notice.