



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Amber Glow / Rainbow Black
OKVIR	Advanced-Grade Composite front and rear triangles, 146mm Maestro suspension, 12x148mm thru-axle
VILICE	Fox 38 Factory Live Valve, 170mm, FIT4 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Factory Live Valve, 205/60, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM GX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle
ZAVORE	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]203mm
ZAVORNE ROČICE	Shimano SLX BL-M7100
VERIŽNIK	SRAM XG-1275 Eagle, 10x52
VERIGA	SRAM GX Eagle
GONILKE Z VERIŽNIKI	TruVativ Descendent 6k, DUB, 32t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TRX 2 29 WheelSystem
PESTA	Giant TRX 2 29 WheelSystem
NAPERE	Giant TRX 2 29 WheelSystem
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, EXO+, TR tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	431	431	464	496
Kot sedežne cevi	76,4°	76,4°	76,4°	76,4°
Top Tube Length (mm)	574	601	640	666
Višina glave okvirja (mm)	100	100	110	120
Krmilni kot	64,6°	64,6°	64,6°	64,6°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	132,7	132,7	132,7	132,7
Medosna razdalja (mm)	1191	1220	1262	1289
Dolžina cevi ob verigi (mm)	439	439	439	439
Bottom Bracket Drop (mm)	27	27	27	27
Oddaljenost zgornje cevi od gonilne osi (mm)	622	622	631	640
Doseg (mm)	423	451	488	511
Višina zgornje cevi (mm)	757	759	781	804
Širina krmila (mm)	800	800	800	800
Dolžina opore krmila (mm)	40	40	40	40
Dolžina gonilke (mm)	165	170	170	170
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.