



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Panther / Phantom Green
FRAME	Advanced-Grade Composite front and rear triangles, 146mm Maestro suspension, 12x148mm thru-axle
FORK	RockShox ZEB Select, 170mm, Charger RC, 15x110 Maxle Stealth, 44mm offset, custom tuned for Giant
SHOCK	RockShox Deluxe Select+, 205/60, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM NX Eagle, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM NX Eagle
BRAKES	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]203mm, [R]203mm
BRAKE LEVERS	Shimano BL-MT501
CASSETTE	SRAM NX Eagle, 11x50
CHAIN	SRAM NX Eagle
CRANKSET	TruVativ Descendent 6k, DUB, 32t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant AM 29, alloy
HUBS	Shimano, sealed
SPOKES	Sapim
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra , EXO+, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	431	431	464	496
Seat Tube Angle	76,4°	76,4°	76,4°	76,4°
Top Tube Length (mm)	574	601	640	666
Head Tube Length (mm)	100	100	110	120
Head Tube Angle	64,6°	64,6°	64,6°	64,6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	132,7	132,7	132,7	132,7
Wheelbase (mm)	1191	1220	1262	1289
Chain Stay Length (mm)	439	439	439	439
Bottom Bracket Drop (mm)	27	27	27	27
Stack (mm)	622	622	631	640
Reach (mm)	423	451	488	511
Stand Over Height (mm)	757	759	781	804
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	40	40	40
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.