



SPECS

QUADRO	
TAMANHOS	S, M, L, XL
CORES	Luminous Lagoon/Chrome
QUADRO	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORQUILHA	RockShox Zeb Ultimate, Charger 3.2 RC2 damper, 170mm, 15x110, Maxle Stealth, Debonair
AMORTECEDORES	RockShox Vivid Ultimate, RCT2, adjustable hydraulic bottom out, trunnion mount, 205/65 S:425#, M:425#, L:450#, XL: 475#
COMPONENTES	
GUIADOR	Giant Contact TR35, 800x35mm, 35mm rise
PUNHOS	Giant Tactal Pro Single
AVANÇO	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
ESPIGÃO DE SELIM	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELIM	Giant Romero SL
TRANSMISSÃO	
MANETES	SRAM AXS Pod, 1x12
DESVIADOR TRASEIRO	SRAM GX AXS Transmission
TRAVÕES	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
MANÍPULOS DOS TRAVÕES	TRP EVO Pro
CASSETTE	SRAM GX Eagle Transmission, 10x52
CORRENTE	SRAM GX Eagle Transmission
CONJUNTO PEDALEIRO	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
CUBOS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
RAIOS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Preço: 6 199,00 €

GEOMETRIA

QUADRO	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Comprimento do tubo do assento (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Ângulo do tubo do assento	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°		
Comprimento do tubo superior (mm)	558	557	556	589	588	587	622	621	621	654	653	652
Comprimento do tubo principal (mm)	100			105			115			120		
Ângulo do tubo principal	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°	63,1°	63,4°
Garfo ancinho (mm)	44			44			44			44		
Trilha (mm)	147	144	141	147	144	141	147	144	141	147	144	141
distância entre eixos (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Comprimento Chain Stay (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Suporte inferior (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Pilha (mm)	633	630	627	638	635	632	647	644	641	652	649	646
Alcançar (mm)	418	421	426	448	452	456	468	471	476	499	503	507
Altura do standover (mm)	714	718	723	733	738	742	746	750	755	762	766	771
Largura do guidão (mm)	800			800			800			800		
Comprimento da haste (mm)	40			40			40			40		
Comprimento da Manivela (mm)	165			170			170			170		
Tamanho da roda	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.