



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Luminous Lagoon/Chrome
OKVIR	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
VILICE	RockShox Zeb Ultimate, Charger 3.2 RC2 damper, 170mm, 15x110, Maxle Stealth, Debonair
AMORTIZER	RockShox Vivid Ultimate, RCT2, adjustable hydraulic bottom out, trunnion mount, 205/65 S:425#, M:425#, L:450#, XL: 475#
KOMPONENTE	
KRMILO	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
OPORA SEDEŽA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDEŽ	Giant Romero SL
POGON	
PRESTAVNE ROČICE	SRAM AXS Pod, 1x12
ZADNJI MENJALNIK	SRAM GX AXS Transmission
ZAVORE	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
ZAVORNE ROČICE	TRP EVO Pro
VERIŽNIK	SRAM GX Eagle Transmission, 10x52
VERIGA	SRAM GX Eagle Transmission
GONILKE Z VERIŽNIKI	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
PESTA	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
NAPERE	Sapim, 28, straight pull, DBL Technology
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, MaxxTerra, DD, TR tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRIJA

OKVIR	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LO
Dolžina sedežne cevi (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	262			287			312			335
Kot sedežne cevi	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°
Top Tube Length (mm)	558	557	556	589	588	587	622	621	621	650
Višina glave okvirja (mm)	100			105			115			120
Krmilni kot	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°
Zamik vpetja osi (mm)	44			44			44			44
Trail (mm)	147	144	141	147	144	141	147	144	141	147
Medosna razdalja (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1300
Dolžina cevi ob verigi (mm)	445	443	442	445	443	442	445	443	442	445
Bottom Bracket Drop (mm)	29	24	19	29	24	19	29	24	19	29
Oddaljenost zgornje cevi od gonilne osi (mm)	633	630	627	638	635	632	647	644	641	650
Doseg (mm)	418	421	426	448	452	456	468	471	476	490
Višina zgornje cevi (mm)	714	718	723	733	738	742	746	750	755	760
Širina krmila (mm)	800			800			800			800
Dolžina opore krmila (mm)	40			40			40			40
Dolžina gonilke (mm)	165			170			170			170
Velikost obročnikov	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.