



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro 2, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 800Wh EnergyPak Plus range extender compatible
CHARGER	EnergyPak 6A smart charger
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, L, XL
COLOURS	Blue Dragonfly / Black
FRAME	ALUXX SL-grade Aluminium, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, flip chip, UDH hanger 12x148mm thru-axle
FORK	Fox 38 Factory E-Tuned, 170mm travel, 44mm offset, GRIP2 VVC damper, Boost Kabolt-X 110x15mm
SHOCK	Fox X2 Factory, EVOL Large Volume sleeve, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact Trail, 35mm
GRIPS	Giant Tactal Pro-E, single lock-on
STEM	Giant Contact SL 35mm S:40mm, M:40mm, L:40mm, XL:50mm
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 559mm XL: 170-200mm travel / 30.9 x 559mm
SADDLE	Giant Romero Trail
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano XT LinkGlide, 1x11
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano XT LinkGlide 11-speed, Shadow+
BRAKES	Shimano XT BR-M8120, 4-piston, hydraulic disc, [F] 220mm, [R] 220mm
BRAKE LEVERS	Shimano XT BL-M8100, I-spec EV
CASSETTE	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
CHAIN	Shimano LinkGlide, CN-LG500
CRANKSET	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm)
BOTTOM BRACKET	N/A

WHEELS	
RIMS	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R], 30mm inner width
HUBS	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano HG Drive Body Pawl Driver (3 Pawl 30T) Thru-axle [R]
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimised
TIRES	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F] Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter

Price: \$11,499.00

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	425	450	475	450	475	450	475
Seat Post Insertion Depth (mm)	230	260	280	310	280	310	280	310
Seat Tube Angle	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°
Top Tube Length (mm)	569 568	595 594	622 621	649 648	622 621	649 648	622 621	649 648
Head Tube Length (mm)	100	100	110	120	100	110	100	110
Head Tube Angle	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°
Fork Rake (mm)	44	44	44	44	44	44	44	44
Trail (mm)	135.5 132.1	135 132	135 132	135.5 132.1	135 132	135.5 132.1	135 132	135.5 132.1
Wheelbase (mm)	1209 1210	1236 1237	1265 1266	1295 1296	1236 1237	1265 1266	1236 1237	1265 1266
Chain Stay Length (mm)	457 455	454 454	454 454	454 454	457 455	454 454	457 455	454 454
Bottom Bracket Drop (mm)	25 15	25 15	25 15	25 15	25 15	25 15	25 15	25 15
Stack (mm)	636 632	635 632	645 641	654 650	636 632	645 641	636 632	654 650
Reach (mm)	425 430	450 455	475 480	500 505	425 430	450 455	475 480	500 505
Stand Over Height (mm)	785 789	772 776	771 775	768 772	785 789	772 776	771 775	768 772
Stem Length (mm)	40	40	40	50	40	40	40	50
Crank Length (mm)	160	160	165	165	160	160	165	165
Wheel Size	29"	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	29"	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.