

REIGN E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATTERY	EnergyPak Smart 625WhEnergyPak Plus range extender compatible
CHARGER	EnergyPak 6A smart charger
FRAME	
SIZES	S, M, L, XL
COLOURS	Good Grey
FRAME	ALUXX SL-grade Aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, UDHTM derailleur hanger
FORK	Fox 38 Float Performance Elite 29er, 170mm travel, GRIP2 VVC Damper, Boost 110x15 Kabolt floating axle, e-Bike optimized
SHOCK	Fox Float X2 Performance Elite, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact Trail, 35x800mm
GRIPS	Giant Tactal Pro-E, single lock-on
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
SADDLE	Giant Romero
PEDALS	Flat pedal
DRIVETRAIN	
SHIFTERS	Shimano Deore XT
FRONT DERAILLEUR	MRP 1X HD2 custom co-molded chain guide
REAR DERAILLEUR	Shimano Deore XT, 12-Speed, Shadow+
BRAKES	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore XT BL-M8100, I-spec EV
CASSETTE	Shimano HG-M7100, 10-51T, 12-speed
CHAIN	KMC e.12 Sport, EcoProteg, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant e-TR1 29"[F] 27.5"[R], Tubeless ready, 30mm inner width
HUBS	Giant e-TR1 [F] 110x15 [R] 148x12mm Thru-axle
SPOKES	Giant e-TR1
TYRES	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable
LOCK	Torx 25 Battery Lock with built-in Torque limiter

Price: €7,899.00

GEOMETRY

FRAME	M
	LOW HIGH
Seat Tube Length (mm)	425
Seat Tube Angle	76.7° 77.5°
Top Tube Length (mm)	595 594
Head Tube Length (mm)	100
Head Tube Angle	63.7° 64.5°
Fork Rake (mm)	44
Trail (mm)	135 132
Wheelbase (mm)	1236 1237
Chain Stay Length (mm)	454 454
Bottom Bracket Drop (mm)	25 15
Stack (mm)	635 632
Reach (mm)	450 455
Stand Over Height (mm)	772 776
Handlebar Width (mm)	800
Stem Length (mm)	40
Crank Length (mm)	160
Wheel Size	F29" / R27

All specifications listed are subject to change without notice.