

REIGN E+ 1

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	SyncDrive Pro 2, 85Nm, powered by Yamaha
MANDO	RideControl GO integrated in TT, RideControl Ergo 3
PANTALLA	Wireless display compatible
BATERÍA	EnergyPak Smart 800, EnergyPak Plus range extender compatible (exclude S Size)
CUADRO	
TALLAS	S, M, L, XL
COLORES	Mirage/Black
CUADRO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, patilla de cambio UDH
HORQUILLA	Fox 38 Float Performance Elite, 29er, 170mm, GRIP2 VVC Damper, Boost 110x15 Kabolt floating axle, with fender, e-Bike optimized
AMORTIGUADOR	Fox Float X2 Performance Elite, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPONENTES	
MANILLAR	Giant Contact SL Trail, 35x800mm
PUÑOS	Giant Tactal Pro-E, single lock-on
POTENCIA	Giant Contact SL 35
TIJA DE SILLÍN	Rad+ travel adjust dropper, dropper, 30,9mm (S:100~140mm, M:140~170mm, L/XL:170~200mm)
SILLÍN	Giant Romero Trail
PEDALES	Flat pedals
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS POD controller
DESVIADOR	MRP 1X HD2 custom co-molded chain guide
CAMBIO TRASERO	SRAM GX Eagle NGD
FRENOS	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
PALANCAS DE FRENOS	SRAM Code R
CASETTE	SRAM GX, 10-52T, 12-speed
CADENA	SRAM GX Eagle PowerLock
JGO. PLATOS Y BIELAS	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)

RUEDAS	
LLANTAS	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
BUJES	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F], 148 x 12 [R] Thru Axle
CUBIERTAS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
LUCES	-
CANDADO/ANTI-ROBO	Torx 25 Battery Lock with built-in Torque limiter
PORTA-EQUIPAJES	-

Precio: 7.999,00 €

GEOMETRÍA

CUADRO	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Longitud del tubo del sillín (mm)	400	425	450
Ángulo del tubo del sillín	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°
Longitud del tubo superior (mm) (mm)	569 568	595 594	622 621
Longitud del tubo de dirección (mm) (mm)	100	100	110
Ángulo del tubo de dirección	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°
Inclinación de la horquilla (mm)	44	44	44
Trail (mm) (mm)	135,5 132,1	135 132	135 132
Distancia entre ejes (mm) (mm)	1209 1210	1236 1237	1265 1266
Longitud de la vaina (mm) (mm)	457 455	454 454	454 454
Caída del eje de pedalier (mm) (mm)	25 15	25 15	25 15
Stack (mm) (mm)	636 632	635 632	645 641
Reach (mm) (mm)	425 430	450 455	475 480
Altura del suelo al tubo (mm) (mm)	785 789	772 776	771 775
Ancho del manillar (mm) (mm)	800	800	800
Longitud de la potencia (mm) (mm)	40	40	50
Longitud de las bielas (mm) (mm)	160	160	165
Tamaño de ruedas	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.