

REIGN E+ 1

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATERÍA	EnergyPak Smart 625WhEnergyPak Plus range extender compatible
CUADRO	
TALLAS	S, M, L, XL
COLORES	Good Grey
CUADRO	ALUXX SL-grade Aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, UDHTM derailleur hanger
TIJERA	Fox 38 Float Performance Elite 29er, 170mm travel, GRIP2 VVC Damper, Boost 110x15 Kabolt floating axle, e-Bike optimized
AMORTIGUADOR	Fox Float X2 Performance Elite, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPONENTES	
MANUBRIO	Giant Contact Trail, 35x800mm
GRIPS	Giant Tactal Pro-E, single lock-on
POTENCIA	Giant Contact SL 35
POSTE DE ASIENTO	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
ASIENTO	Giant Romero
PEDALES	Flat pedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore XT
DESVIADOR	MRP 1X HD2 custom co-molded chain guide
CAMBIO TRASERO	Shimano Deore XT, 12-Speed, Shadow+
FRENOS	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 203mm
PALANCAS DE FRENOS	Shimano Deore XT BL-M8100, I-spec EV
CASSETTE	Shimano HG-M7100, 10-51T, 12-speed
CADENA	KMC e.12 Turbo o KMC e Sport, EcoProteg, e-bike optimized
MULTIPLICACIÓN	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)
EJE DE CENTRO	N/A

RUEDAS	
RUEDAS	Giant e-TR1 29"[F] 27.5"[R], Tubeless ready, 30mm inner width
MAZAS	Giant e-TR1 [F] 110x15 [R] 148x12mm Thru-axle
RAYOS	Giant e-TR1
NEUMÁTICOS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
LUCES	Optional:- Giant Recon series e-bike lights available and direct connectable

Precio: \$179,900.00

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400		425		450		475	
Ángulo de la Base del Poste de Asiento	76.7°	77.5°	76.7°	77.5°	76.7°	77.5°	76.7°	77.5°
Longitud del Tubo Superior (mm)	569	568	595	594	622	621	649	648
Longitud del Telescopio (mm)	100		100		110		120	
Ángulo del Telescopio	63.7°	64.5°	63.7°	64.5°	63.7°	64.5°	63.7°	64.5°
Rake (mm)	44		44		44		44	
Trail (mm)	135.5	132.1	135	132	135	132	135.5	132.1
Distancia entre Ejes (mm)	1209	1210	1236	1237	1265	1266	1295	1296
Longitud de Vaina Inferior (mm)	454	454	454	454	454	454	454	454
Caída del Eje de Centro (mm)	25	15	25	15	25	15	25	15
Stack (mm)	636	632	635	632	645	641	654	650
Reach (mm)	425	430	450	455	475	480	500	505
Altura del Tubo Superior al Suelo (mm)	785	789	772	776	771	775	768	772
Ancho del Manubrio (mm)	800		800		800		800	
Longitud de la Potencia (mm)	40		40		50		50	
Longitud de la Biela (mm)	160		160		165		165	
Tamaño de las Ruedas	F29" / R27		F29" / R27		F29" / R27		F29" / R27	

Todas las especificaciones están sujetas a cambios sin previo aviso.