



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATERÍA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exculde S size)
CHARGER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	S, M, L, XL
COLORES	Blue Dragonfly / Black
CUADRO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
TIJERA	Fox 38 Float Factory GRIP 2 Air 170 matt black 1111-38FLOA-0024
AMORTIGUADOR	Fox X2 Factory, EVOL Large Volume sleeve, 205x62.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTES	
MANUBRIO	Giant Contact Trail, 35x800mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCIA	Giant Contact SL 35
POSTE DE ASIENTO	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
ASIENTO	Giant Romero Trail
PEDALES	Flat pedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano XT LinkGlide
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	Shimano XT LinkGlide 11-speed, Shadow+
FRENOS	Shimano XT, BR-8120, 4-piston, hydraulic disc, RT66, 220mm
PALANCAS DE FRENOS	Shimano XT, I-spec EV
CASSETTE	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
CADENA	Shimano LinkGlide, CN-LG500
MULTIPLICACIÓN	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm)
EJE DE CENTRO	n/a

RUEDAS	
RUEDAS	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R], 30mm inner width
MAZAS	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano HG Drive Body Pawl Driver (3 Pawl 30T) Thru-axle [R]
RAYOS	Sapim E-Lite [R] Race [F], e-bike optimized
NEUMÁTICOS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F] Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
CANDADOS	Torx 25 Battery Lock with built-in Torque limiter

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400	425	450	475				
Seat Post Insertion Depth (mm)	235	260	285	310				
Ángulo de la Base del Poste de Asiento	76.7°	77.5°	76.7°	77.5°	76.7°	77.5°	76.7°	77.5°
Longitud del Tubo Superior (mm)	569	568	595	594	622	621	649	648
Longitud del Telescopio (mm)	100	100	110	120				
Ángulo del Telescopio	63.7°	64.5°	63.7°	64.5°	63.7°	64.5°	63.7°	64.5°
Rake (mm)	44	44	44	44				
Trail (mm)	135.5	132.1	135	132	135	132	135.5	132.1
Distancia entre Ejes (mm)	1209	1210	1236	1237	1265	1266	1295	1296
Longitud de Vaina Inferior (mm)	457	455	454	454	454	454	454	454
Caída del Eje de Centro (mm)	25	15	25	15	25	15	25	15
Stack (mm)	636	632	635	632	645	641	654	650
Reach (mm)	425	430	450	455	475	480	500	505
Altura del Tubo Superior al Suelo (mm)	785	789	772	776	771	775	768	772
Ancho del Manubrio (mm)	800	800	800	800				
Longitud de la Potencia (mm)	40	40	40	50				
Longitud de la Biela (mm)	160	160	165	165				
Tamaño de las Ruedas	29"		[F] 29" [R]		[F] 29" [R]		[F] 29" [R]	

Todas las especificaciones están sujetas a cambios sin previo aviso.