



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	SyncDrive Pro, 85Nm, powered by Yamaha
COMMANDE	RideControl GO integrated in TT, RideControl Ergo 3
ECRAN	Wireless display compatible
BATTERIE	EnergyPak Smart 800, EnergyPak Plus range extender compatible (exclude S Size)
CADRE	
TAILLES	S, M, L, XL
COLORIS	Mirage/Black
CADRE	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Deraillieur Hanger
FOURCHE	Fox 38 Float Performance Elite, 29er, 170mm, GRIP2 VVC Damper, Boost 110x15 Kabolt floating axle, with fender, e-Bike optimized
AMORTISSEUR	Fox Float X2 Performance Elite, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact SL Trail, 35x800mm
POIGNÉES	Giant Tactal Pro-E, single lock-on
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Rad+ travel adjust dropper, dropper, 30,9mm (S:100-140mm, M:140-170mm, L/XL:170-200mm)
SELLE	Giant Romero Trail
PÉDALES	Flat pedals
DÉRAILLEUR	
MANETTES	SRAM AXS Rocker Paddle, wireless electronic shifting
DÉRAILLEUR AVANT	MRP 1X HD2 custom co-molded chain guide
DÉRAILLEUR ARRIÈRE	SRAM GX Eagle AXS
FREINS	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
LEVIERS DE FREIN	SRAM Code R
CASSETTE	SRAM XG-1275, 10-52T, 12-speed
CHAÎNE	SRAM GX Eagle PowerLock
PÉDALIER	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)

ROUES	
JANTES	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
MOYEUX	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 24T) SRAM XD, 110 x 15 [F], 148 x 12 [R] Thru Axle
PNEUS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
ANTI-VOL	Torx 25 Battery Lock with built-in Torque limiter
PORTE-BAGAGES	-
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 8 200,00 €

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475	450	475	450	475
Angle de tube de selle	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°
Longueur du tube supérieur (mm)	569 568	595 594	622 621	649 648	569 568	595 594	622 621	649 648
Longueur du tube de direction (mm)	100	100	110	120	100	100	110	120
Angle du tube de direction	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°
Déport de fourche (mm)	44	44	44	44	44	44	44	44
Trail (mm)	135,5 132,1	135 132	135 132	135,5 132,1	135,5 132,1	135 132	135,5 132,1	135,5 132,1
Empattement (mm)	1209 1210	1236 1237	1265 1266	1295 1296	1209 1210	1236 1237	1265 1266	1295 1296
Longueur des bases (mm)	457 455	454 454	454 454	454 454	457 455	454 454	454 454	454 454
Drop du boîtier de pédalier (mm)	25 15	25 15	25 15	25 15	25 15	25 15	25 15	25 15
Stack (mm)	636 632	635 632	645 641	654 650	636 632	635 632	645 641	654 650
Reach (mm)	425 430	450 455	475 480	500 505	425 430	450 455	475 480	500 505
Hauteur en statique (mm)	785 789	772 776	771 775	768 772	785 789	772 776	771 775	768 772
Largeur de cintre (mm)	800	800	800	800	800	800	800	800
Longueur de potence (mm)	40	40	50	50	40	40	50	50
Longueur des manivelles (mm)	160	160	165	165	160	160	165	165
Diamètre des roues	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.