

REIGN E+ 1

GIANT



SPECS

Tecnologia Híbrida de Ciclismo	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl GO integrated in TT, RideControl Ergo 3
ECRÃ	Wireless display compatible
BATERIA	EnergyPak Smart 800, EnergyPak Plus range extender compatible (exclude S Size)
Quadro	
TAMANHOS	S, M, L, XL
CORES	Mirage/Black
QUADRO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
FORQUILHA	Fox 38 Float Performance Elite, 29er, 170mm, GRIP2 VVC Damper, Boost 110x15 Kabolt floating axle, with fender, e-Bike optimized
AMORTECEDORES	Fox Float X2 Performance Elite, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
Componentes	
GUIADOR	Giant Contact SL Trail, 35x800mm
PUNHOS	Giant Tactal Pro-E, single lock-on
AVANÇO	Giant Contact SL 35
ESPIGÃO DE SELIM	Rad+ travel adjust dropper, dropper, 30,9mm (S:100~140mm, M:140~170mm, L/XL:170~200mm)
SELIM	Giant Romero Trail
PEDAIS	Flat pedals
Transmissão	
MANETES	SRAM AXS POD controller
DESVIADOR DIANTEIRO	MRP 1X HD2 custom co-molded chain guide
DESVIADOR TRASEIRO	SRAM GX Eagle NGD
TRAVÕES	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
MANÍPULOS DOS TRAVÕES	SRAM Code R
CASSETTE	SRAM GX, 10-52T, 12-speed
CORRENTE	SRAM GX Eagle PowerLock
CONJUNTO PEDALEIRO	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)

Rodas	
AROS	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
CUBOS	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F], 148 x 12 [R] Thru Axle
PNEUS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
Acessórios	
LUZES	-
CADEADO	Torx 25 Battery Lock with built-in Torque limiter
PORTA-BICICLETAS	-

Preço: 6 999,00 €

GEOMETRIA

Quadro	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Comprimento do tubo do assento (mm)	400	425	450
Ângulo do tubo do assento	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°
Comprimento do tubo superior (mm)	569 568	595 594	622 621
Comprimento do tubo principal (mm)	100	100	110
Ângulo do tubo principal	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°
Garfo ancinho (mm)	44	44	44
Trilha (mm)	135,5 132,1	135 132	135 132
distância entre eixos (mm)	1209 1210	1236 1237	1265 1266
Comprimento Chain Stay (mm)	457 455	454 454	454 454
Suporte inferior (mm)	25 15	25 15	25 15
Pilha (mm)	636 632	635 632	645 641
Alcançar (mm)	425 430	450 455	475 480
Altura do standover (mm)	785 789	772 776	771 775
Largura do guidão (mm)	800	800	800
Comprimento da haste (mm)	40	40	50
Comprimento da Manivela (mm)	160	160	165
Tamanho da roda	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.