

REIGN E+ 1

GIANT



SPECS

Tecnologia Híbrida de Ciclismo	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
ECRÃ	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATERIA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exculde S size)
CARREGADOR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
Quadro	
TAMANHOS	S, M, L, XL
CORES	Blue Dragonfly / Black
QUADRO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
FORQUILHA	Fox 38 Float Factory GRIP 2 Air 170 matt black 1111-38FLOA-0024
AMORTECEDORES	Fox X2 Factory, EVOL Large Volume sleeve, 205x62.5mm Trunnion mount, custom tuned, recommended sag: 30%
Componentes	
GUIADOR	Giant Contact Trail, 35x800mm
PUNHOS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
AVANÇO	Giant Contact SL 35
ESPIGÃO DE SELIM	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELIM	Giant Romero Trail
PEDAIS	Flat pedal
Transmissão	
MANETES	Shimano XT LinkGlide
DESVIADOR DIANTEIRO	MRP HD2 co-moulded chain guide
DESVIADOR TRASEIRO	Shimano XT LinkGlide 11-speed, Shadow+
TRAVÕES	Shimano XT, BR-8120, 4-piston, hydraulic disc, RT66, 220mm
MANÍPULOS DOS TRAVÕES	Shimano XT, I-spec EV
CASSETTE	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
CORRENTE	Shimano LinkGlide, CN-LG500
CONJUNTO PEDALEIRO	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm)
MOVIMENTO CENTRAL	n/a

Rodas	
AROS	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R], 30mm inner width
CUBOS	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano HG Drive Body Pawl Driver (3 Pawl 30T) Thru-axle [R]
RAIOS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29x2.6''' foldable, Tubeless, EXO+, 3C MaxxTerra[F] Maxxis High Roller II 27.5x2.5''' foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
Acessórios	
CADEADO	Torx 25 Battery Lock with built-in Torque limiter

Preço: 6 149,00 €

GEOMETRIA

Quadro	S
	LOW HIGH
Comprimento do tubo do assento (mm)	400
Seat Post Insertion Depth (mm)	235
Ângulo do tubo do assento	76,7° 77,5°
Comprimento do tubo superior (mm)	569 568
Comprimento do tubo principal (mm)	100
Ângulo do tubo principal	63,7° 64,5°
Garfo ancinho (mm)	44
Trilha (mm)	135,5 132,1
distância entre eixos (mm)	1209 1210
Comprimento Chain Stay (mm)	457 455
Suporte inferior (mm)	25 15
Pilha (mm)	636 632
Alcançar (mm)	425 430
Altura do standover (mm)	785 789
Largura do guidão (mm)	800
Comprimento da haste (mm)	40
Comprimento da Manivela (mm)	160
Tamanho da roda	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.