



TECHNIQUES

| TECHNOLOGIE HYBRID | |
|----------------------------|--|
| MOTEUR | Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology |
| COMMANDE | Giant RideControl Ergo3, grip integrated remote |
| ECRAN | Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display |
| BATTERIE | Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exclue S size) |
| CHARGEUR | Giant EnergyPak 6A smart charger, 60% in 2:15h |
| CONNECTIVITÉ | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile |
| CADRE | |
| TAILLES | S, M, L, XL |
| COLORIS | Sangria / Black |
| CADRE | ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, "Boost" 148x12mm, Universal Derailleur Hanger |
| FOURCHE | Fox 38 Rhythm E-Optimized, 29er, 170mm travel, 44mm offset, Grip damper Sweep-Adj Boost, Kabolt-X 110 |
| AMORTISSEUR | Fox Float X Performance, EVOL Large Volume sleeve, 205x62.5mm Trunnion mount, custom tuned, recommended sag: 30% |
| COMPOSANTS | |
| CINTRE | Giant Contact Trail, 35x800mm |
| POIGNÉES | Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL) |
| POTENCE | Giant Contact SL 35 |
| TIGE DE SELLE | OBC Giant Contact Switch AT Travel adjustable 172D-CONTAC-0053 total length 315 T100-70MM / 172D-CONTAC-0052 total length 395 T140-110MM / 172D-CONTAC-0051 total length 470 T170-140MM / 172D-CONTAC-0050 total length 530 T200-170MM |
| SELLE | Velo VL3594 |
| PÉDALES | Flatpedal |
| DÉRAILLEUR | |
| MANETTES | Shimano Cues LinkGlide |
| DÉRAILLEUR AVANT | MRP 1X HD2 custom co-molded chain guide |
| DÉRAILLEUR ARRIÈRE | Shimano Cues LinkGlide 11-speed |
| FREINS | Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 220mm[F], 203mm [R] |
| LEVIER DE FREIN | Shimano Deore, I-spec EV |
| CASSETTE | Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed |
| CHAÎNE | Shimano LinkGlide, CN-LG500 |
| PÉDALIER | Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm) |
| BOITIER DE PÉDALIER | n/a |

| ROUES | |
|---------------------------------|---|
| JANTES | Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R] |
| MOYEUX | Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm HG Drive Body Thru-axle |
| RAYONS | Sapim E-Lite [R] Race [F], e-bike optimized |
| PNEUS | Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F] Maxxis Assagai 27.5x2.5" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R] 1560-ASSEGA-0014 |
| EXTRAS | Tubeless kit (liquid, valves, levers, manual, tool) |
| ACCESSOIRES | |
| ECLAIRAGE | Kit d'éclairage avant et arrière à piles |
| ANTI-VOL | Torx 25 Battery Lock with built-in Torque limiter |
| LIMITES | |
| POIDS TOTAL MAX AUTORISÉ | 156 kg (vélo, cycliste et bagages) |

Prix Public Conseillé: 6 100,00 €

GÉOMÉTRIE

| CADRE | S | | M | | L | | XL | |
|------------------------------------|---------------|---------------|---------------|---------------|-----|------|-----|------|
| | LOW | HIGH | LOW | HIGH | LOW | HIGH | LOW | HIGH |
| Longueur de tube de selle (mm) | 400 | 425 | 450 | 475 | | | | |
| Seat Post Insertion Depth (mm) | 230 | 260 | 280 | 310 | | | | |
| Angle de tube de selle | 76,7° 77,5° | 76,7° 77,5° | 76,7° 77,5° | 76,7° 77,5° | | | | |
| Longueur du tube supérieur (mm) | 569 568 | 595 594 | 622 621 | 649 648 | | | | |
| Longueur du tube de direction (mm) | 100 | 100 | 110 | 120 | | | | |
| Angle du tube de direction | 63,7° 64,5° | 63,7° 64,5° | 63,7° 64,5° | 63,7° 64,5° | | | | |
| Déport de fourche (mm) | 44 | 44 | 44 | 44 | | | | |
| Trail (mm) | 135,5 132,1 | 135 132 | 135 132 | 135,5 132,1 | | | | |
| Empattement (mm) | 1209 1210 | 1236 1237 | 1265 1266 | 1295 1296 | | | | |
| Longueur des bases (mm) | 457 455 | 454 454 | 454 454 | 454 454 | | | | |
| Drop du boîtier de pédalier (mm) | 25 15 | 25 15 | 25 15 | 25 15 | | | | |
| Stack (mm) | 636 632 | 635 632 | 645 641 | 654 650 | | | | |
| Reach (mm) | 425 430 | 450 455 | 475 480 | 500 505 | | | | |
| Hauteur en statique (mm) | 785 789 | 772 776 | 771 775 | 768 772 | | | | |
| Largeur de cintre (mm) | 800 | 800 | 800 | 800 | | | | |
| Longueur de potence (mm) | 40 | 40 | 40 | 50 | | | | |
| Longueur des manivelles (mm) | 160 | 160 | 165 | 165 | | | | |
| Diamètre des roues | 29" | [F] 29" [R] | [F] 29" [R] | [F] 29" [R] | | | | |

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.