



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	SyncDrive Pro, 85Nm, powered by Yamaha
COMANDO	RideControl GO integrated in TT, RideControl Ergo 3
DISPLAY	Wireless display compatible
BATTERIA	EnergyPak Smart 800,EnergyPak Plus range extender compatible (exclude S Size)
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Cordovan/Black
TELAIO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
FORCELLA	RockShox ZEB Select 29er, 170mm travel, Charger RC damper, 15x110 Boost, Maxle Stealth, E-bike Approved
AMMORTIZZATORE	Fox Float X Performance, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Contact Trail, 35x800mm
MANOPOLE	Giant Tactal Pro-E, single lock-on
ATTACCO MANUBRIO	Giant Contact SL 35
REGGISELLA	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SELLA	Giant Romero Trail
PEDALI	Flat pedal
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore SLX
DERAGLIATORE ANTERIORE	MRP HD2 co-moulded chain guide
DERAGLIATORE POSTERIORE	Shimano Deore SLX, 12-speed, Shadow+
FRENI	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
COMANDI FRENO	Shimano SLX, I-spec EV
PACCO PIGNONI	Shimano HG-M6100, 10-51T, 12-speed
CATENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GUARNITURA	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)
MOVIMENTO CENTRALE	n/a

RUOTE	
CERCHI	Giant AM 29" [F] 27.5"[R], Tubeless ready, 30mm inner width
MOZZI	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAGGI	Sapim E-Lite [R] Race [F], e-bike optimized
COPERTONI	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRA	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
ILLUMINAZIONE	-
LUCCHETTO	Torx 25 Battery Lock with built-in Torque limiter
PORTAPACCHI	-

Prezzo: 5.999,00 €

GEOMETRIA

TELAIO	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Lunghezza Tubo Sella (mm)	400	425	450	475
Angolo Tubo Sella	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°	76,7° 77,5°
Lunghezza Tubo Orizzontale (mm)	569 568	595 594	622 621	649 648
Lunghezza Tubo Sterzo (mm)	100	100	110	120
Angolo Sterzo	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°	63,7° 64,5°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	135,5 132,1	135 132	135 132	135,5 132,1
Interasse (mm)	1209 1210	1236 1237	1265 1266	1295 1296
Lunghezza Carro Posteriore (mm)	457 455	454 454	454 454	454 454
Drop Movimento Centrale (mm)	25 15	25 15	25 15	25 15
Stack (mm)	636 632	635 632	645 641	654 650
Reach (mm)	425 430	450 455	475 480	500 505
Altezza stand over (mm)	785 789	772 776	771 775	768 772
Larghezza Manubrio c/c (mm)	800	800	800	800
Lunghezza Attacco Manubrio (mm)	40	40	50	50
Lunghezza Pedivella (mm)	160	160	165	165
Dimensione Ruote	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.