



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	Wireless display compatible
BATTERY	EnergyPak Smart 800, EnergyPak Plus range extender compatible (exclude S Size)
FRAME	
SIZES	S, M, L, XL
COLOURS	Cobalt/Black
FRAME	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
FORK	RockShox Domain R 29er, 170mm travel, 15x110 Boost, Maxle Stealth, E-bike Approved
SHOCK	Fox Float DPS Performance, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact Trail
GRIPS	Giant Tactal Pro-E, single lock-on
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch, dropper
SADDLE	Giant Romero Trail
PEDALS	Flat pedal
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	MRP 1X HD2 custom co-molded chain guide
REAR DERAILLEUR	Shimano Deore 12-speed
BRAKES	Shimano Deore BR-M420, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore, I-spec EV
CASSETTE	Shimano Deore CS-M6100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant AM 29" [F] 27.5" [R]
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimized
TIRES	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	-
LOCK	Torx 25 Battery Lock with built-in Torque limiter
CARRIER	-

Price: \$7,999.00

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	425	450	475				
Seat Tube Angle	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°				
Top Tube Length (mm)	569 568	595 594	622 621	649 648				
Head Tube Length (mm)	100	100	110	120				
Head Tube Angle	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	135.5 132.1	135 132	135 132	135.5 132.1				
Wheelbase (mm)	1209 1210	1236 1237	1265 1266	1295 1296				
Chain Stay Length (mm)	457 455	454 454	454 454	454 454				
Bottom Bracket Drop (mm)	25 15	25 15	25 15	25 15				
Stack (mm)	636 632	635 632	645 641	654 650				
Reach (mm)	425 430	450 455	475 480	500 505				
Stand Over Height (mm)	785 789	772 776	771 775	768 772				
Stem Length (mm)	40	40	50	50				
Crank Length (mm)	160	160	165	165				
Wheel Size	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.