

REIGN E+ 3

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
MANDO	Giant RideControl Ergo3, grip integrated remote
PANTALLA	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exculde S size)
CARGADOR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	S, M, L, XL
COLORES	Raw Aluminum / Black
CUADRO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Deraillieur Hanger
HORQUILLA	SR Suntour DuroLux 38 Boost EQ, 170mm travel, 44mm offset, RC2, 15LH-110
AMORTIGUADOR	Fox Float Performance, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTES	
MANILLAR	Giant Contact Trail, 35x800mm
PUÑOS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCIA	Giant Contact SL 35
TIJA DE SILLÍN	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/L:170/XL:200)
SILLÍN	Giant Romero Trail
PEDALES	Flatpedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Cues LinkGlide
DESVIADOR	MRP 1X HD2 custom co-molded chain guide
CAMBIO TRASERO	Shimano Cues LinkGlide 11-speed
FRENOS	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm
PALANCAS DE FRENOS	Shimano Deore, I-spec EV
CASETTE	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
CADENA	Shimano LinkGlide, CN-LG500
JGO. PLATOS Y BIELAS	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm)
CAJA DE PEDALIER	n/a

RUEDAS	
LLANTAS	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
BUJES	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm HG Drive Body Thru-axle
RADIOS	Sapim E-Lite [R] Race [F], e-bike optimized
CUBIERTAS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F] Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
CANDADO/ANTI-ROBO	Torx 25 Battery Lock with built-in Torque limiter

Precio: 4.999,00 €

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud del tubo del sillín (mm)	400		425		450		475	
Seat Post Insertion Depth (mm)	235		260		285		310	
Ángulo del tubo del sillín	76,7°	77,5°	76,7°	77,5°	76,7°	77,5°	76,7°	77,5°
Longitud del tubo superior (mm) (mm)	569	568	595	594	622	621	649	648
Longitud del tubo de dirección (mm) (mm)	100		100		110		120	
Ángulo del tubo de dirección	63,7°	64,5°	63,7°	64,5°	63,7°	64,5°	63,7°	64,5°
Inclinación de la horquilla (mm)	44		44		44		44	
Trail (mm) (mm)	135,5	132,1	135	132	135	132	135,5	132,1
Distancia entre ejes (mm) (mm)	1209	1210	1236	1237	1265	1266	1295	1296
Longitud de la vaina (mm) (mm)	457	455	454	454	454	454	454	454
Caída del eje de pedalier (mm) (mm)	25	15	25	15	25	15	25	15
Stack (mm) (mm)	636	632	635	632	645	641	654	650
Reach (mm) (mm)	425	430	450	455	475	480	500	505
Altura del suelo al tubo (mm) (mm)	785	789	772	776	771	775	768	772
Ancho del manillar (mm) (mm)	800		800		800		800	
Longitud de la potencia (mm) (mm)	40		40		40		50	
Longitud de las bielas (mm) (mm)	160		160		165		165	
Tamaño de ruedas	29"		[F] 29" [R]		[F] 29" [R]		[F] 29" [R]	

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.